Burch



Repeats Not Shown to Scale.

Zest Lemon 1007955

Meets or exceeds all ACT® Standards

Made in the USA Crypton Seating Fabric Bleach Cleanable



*ACT® Registered Certification Marks

Fabric Specifications

| Content 100% Polyester Finish Crypton Backing Crypton Bleach Cleanable Yes Ratio: 90% Water / 10% Bleach Solution Weight 14.22 oz. per linear yd Width 54" Roll Size 60 yards Ends: 30 per inch Picks: 128 per inch Repeat H - 1.375 " V - 1.375 " V - 1.375 " Directional Yes Railroaded No Made in the USA Yes | | |
|--|------------------|-------------------------|
| Backing Crypton | Content | 100% Polyester |
| Bleach Cleanable Yes Ratio: 90% Water / 10% Bleach Solution Weight 14.22 oz. per linear yd Width 54" Roll Size 60 yards Ends/Picks Ends: 30 per inch Picks: 128 per inch Repeat H - 1.375 " V - 1.375 " Directional Yes Railroaded No | Finish | Crypton |
| Ratio: 90% Water / 10% Bleach Solution Weight 14.22 oz. per linear yd Width 54" Roll Size 60 yards Ends/Picks Ends: 30 per inch Picks: 128 per inch Repeat H - 1.375 " V - 1.375 " Directional Yes Railroaded No | Backing | Crypton |
| Width 54" Roll Size 60 yards Ends/Picks Ends: 30 per inch Picks: 128 per inch Repeat H - 1.375 " V - 1.375 " Directional Yes Railroaded No | Bleach Cleanable | |
| Roll Size 60 yards Ends/Picks Ends: 30 per inch Picks: 128 per inch Repeat H - 1.375 " V - 1.375 " Directional Yes Railroaded No | Weight | 14.22 oz. per linear yd |
| Ends/Picks | Width | 54" |
| Picks: 128 per inch Repeat H - 1.375 " V - 1.375 " Directional Yes Railroaded No | Roll Size | 60 yards |
| V - 1.375 " Directional Yes Railroaded No | Ends/Picks | |
| Railroaded No | Repeat | |
| | Directional | Yes |
| Made in the USA Yes | Railroaded | No |
| | Made in the USA | Yes |

Certifications

| Greenguard Gold Yes - Crypton Technology is Greenguard Gold Certified Certified | 9 | ,, 3, 3 |
|---|---|---------|
|---|---|---------|

Recommended Cleaning

Please refer to Detailed Cleaning Instructions.

Performance Characteristics

| Abrasion Resistance ASTM D4157 | 50,000 double rubs* | | |
|-----------------------------------|--------------------------------------|--|--|
| Brush Pill ASTM D3511 | 5 | | |
| Tensile Strength ASTM D5034 | Warp: 279.6 lbs. Fill: 366.9 lbs. | | |
| Tear Strength ASTM D2261-07 | Warp: 43.5 lbs. Fill: 27.1 lbs. | | |
| Seam Slippage ASTM D1683-07 | Warp: 28.7 lbs. Fill: 114.6 lbs. | | |
| Colorfastness to Crocking AATCC 8 | Dry: 5.0 Wet: Not Tested | | |
| Colorfastness to Light AATCC 16 | Hours: 40.0 Class: 4.5 | | |
| Flammability** | | | |
| CAL TB 117-2013 | Passes | | |
| NFPA 260 | Class 1 | | |
| UFAC | Class 1 | | |
| | | | |

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

 $\label{product} Final\ determination\ of\ the\ suitability\ of\ this\ product\ for\ an\ application\ rests\ with\ the\ user.$

- * Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.
- $\star\star$ This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.