
# Burch



Repeats Not Shown to Scale.

## Fabric Specifications

77% Polyester 15% Post Industrial Recycled Polyester 8% Post Consumer Recycled Polyester
Crypton
Crypton
Yes Ratio: 90% Water / 10% Bleach Solution
16.04 oz. per linear yd
54"
50 yards
Ends: 160 per inch Picks: 73 per inch
H - 7.313 " V - 7.438 "
Yes
No
Yes

# Trek Charcoal 1008095

Meets or exceeds all ACT<sup>®</sup> Standards

Made in the USA Crypton Seating Fabric Bleach Cleanable PFAS Free stock may be available



\*ACT<sup>®</sup> Registered Certification Marks

# **Performance Characteristics**

Abrasion Resistance ASTM D4157	80,000 double rubs*
Brush Pill ASTM D3511	5
Tensile Strength ASTM D5034	Warp: 230.0 lbs. Fill: 309.0 lbs.
Tear Strength ASTM D2262	Warp: 40.0 lbs. Fill: 67.0 lbs.
Seam Slippage ASTM D4034	Warp: 51.0 lbs. Fill: 89.0 lbs.
Colorfastness to Crocking AATCC 8	Dry: 5.0 Wet: 4.5
Colorfastness to Light AATCC 16	Hours: 40.0 Class: 4.0
Flammability**	
CAL TB 117-2013	Passes
NFPA 260	Class 1
UFAC	Class 1

### Additional Attributes

PFAS Free	In transition to PFAS Free Sku-Dependent Contact Customer Care	
Certifications		
Greenguard Gold Certified	Yes - Crypton Technology is Greenguard Gold Certified	
Recommended Cleaning		
Please refer to Detailed	Cleaning Instructions.	

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

\* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

\*\* This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Toll Free 1.800.841.8111

Visit us at BurchFabrics.com