



Repeats Not Shown to Scale

## **Tether Sprout** 1010080

Meets or exceeds all ACT® Standards

Made in the USA Nanotex Seating Fabric Bleach Cleanable PFAS Free stock may be available



\*ACT® Registered Certification Marks

## **Fabric Specifications**

Content	91% Polyester 6% Post Industrial Recycled Polyester 3% Post Consumer Recycled Polyester
Finish	Nanotex
Backing	Acrylic
Bleach Cleanable	Yes Ratio: 90% Water / 10% Bleach Solution
Weight	10.4 oz. per linear yd
Width	54"
Roll Size	50 yards
Ends/Picks	Ends: 160 per inch Picks: 40 per inch
Repeat	H - 2.5 " V - 0.625 "
Directional	Yes
Railroaded	No
Made in the USA	Yes

## Performance Characteristics

Abrasion Resistance ASTM D4157	51,000 double rubs*	
Brush Pill ASTM D3511	4	
Tensile Strength ASTM D5034	Warp: 154.0 lbs. Fill: 165.0 lbs.	
Tear Strength ASTM D2261	Warp: 9.0 lbs. Fill: 34.0 lbs.	
Seam Slippage ASTM D4034	Warp: 36.0 lbs. Fill: 66.0 lbs.	
Colorfastness to Crocking AATCC 8	Dry: 4.0 Wet: 3.0	
Colorfastness to Light AATCC 16	Hours: 40.0 Class: 4.0	
Flammability**		
CAL TB 117-2013	Passes	
NFPA 260	Class 1	
UFAC	Class 1	

## **Additional Attributes**

PFAS Free	In transition to PFAS Free Sku-Dependent Contact Customer Care		
High Performance	Yes		
Certifications			
Greenguard Gold Certified	Yes		
Recommended Cleaning			
Please refer to Detailed Cleaning Instructions.			

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

- \* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.
- \*\* This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Toll Free 1.800.841.8111

Visit us at BurchFabrics.com