Burch



Repeats Not Shown to Scale

Empire Brassworks 1011323

Meets or exceeds all ACT® Standards

Made in the USA Nanotex Seating Fabric Bleach Cleanable PFAS Free stock may be available



*ACT® Registered Certification Marks

Fabric Specifications

87% Post Consumer Recycled Polyester 13% Nylon
Nanotex
Acrylic
Yes Ratio: 90% Water / 10% Bleach Solution
25.3 oz. per linear yd
54"
60 yards
Ends: 160 per inch Picks: 157 per inch
H - 9.75 " V - 13.88 "
Yes
No
Yes

Performance Characteristics

Abrasion Resistance ASTM D4157	102,000 double rubs*
Brush Pill ASTM D3511	4
Tensile Strength ASTM D5034	Warp: 313.0 lbs. Fill: 460.0 lbs.
Tear Strength ASTM D2261	Warp: 24.0 lbs. Fill: 36.0 lbs.
Seam Slippage ASTM D4034	Warp: 89.0 lbs. Fill: 52.0 lbs.
Colorfastness to Crocking AATCC 8	Dry: 4.0 Wet: 3.0
Colorfastness to Light AATCC 16	Hours: 40.0 Class: 4.0
Flammability**	
CAL TB 117-2013	Passes
NFPA 260	Class 1
UFAC	Class 1

Additional Attributes

PFAS Free	In transition to PFAS Free Sku-Dependent Contact Customer Care	
High Performance	Yes	
HPD on File	Yes	
Certifications		
Greenguard Gold Certified	Yes	
Recommended Cleaning		
Please refer to Detailed Cleaning Instructions.		

Final determination of the suitability of this product for an application rests with the user.

- * Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.
- ** This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Toll Free 1.800.841.8111

Visit us at BurchFabrics.com