



Repeats Not Shown to Scale.

Whisper Forest 0229

Meets or exceeds all ACT® Standards

High Performance Vinyl
Ink Cleanable
Denim Dye Cleanable
Bleach Cleanable
FR Free – Compliant with CAL AB 2998
PFAS Free



*ACT® Registered Certification Marks

Fabric Specifications

| | |
|-------------------|---|
| Face | 100% Vinyl |
| Backing | 100% Polyester |
| Finish/Treatment | Permablok® Plus + |
| Bleach Cleanable | Yes Ratio: 90% Water / 10% Bleach Solution |
| Weight | 27.0 oz. per linear yd |
| Thickness | 1.14 mm |
| Width | 54" |
| Roll Size | 30 yards |
| Directional | Yes |
| Railroaded | No |
| Country of Origin | Costa Rica |

Additional Attributes

| | |
|---|-----|
| Ink Cleanable | Yes |
| Denim Dye Cleanable | Yes |
| PFAS Free | Yes |
| Prop 65 Compliant | Yes |
| Free of Added FR Chemicals / CAL AB2998 Compliant | Yes |
| Antibacterial | Yes |
| Antimicrobial | Yes |
| BPA Free | Yes |
| Free of Conflict Minerals | Yes |
| Formaldehyde Free | Yes |
| Free of Heavy Metals | Yes |
| Lead Free | Yes |
| Sulfide Stain Resistant | Yes |

Performance Characteristics

| | |
|---|-------------------------------------|
| Abrasion Resistance <small>ASTM D4157</small> | 100,000 double rubs* |
| Tensile Strength <small>CFFA-17</small> | Warp: 121.0 lbs. Fill: 72.0 lbs. |
| Tear Strength <small>CFFA-16</small> | Warp: 16.0 lbs. Fill: 18.0 lbs. |
| Seam Slippage <small>DIN 54301</small> | Warp: 46.0 lbs. Fill: 35.0 lbs. |
| Colorfastness to Crocking <small>CFFA-7</small> | Dry: 3.5 Wet: 4.0 |
| UV Resistance <small>AATCC TM 16E</small> | 1000 hours |
| Adhesion <small>CFFA-3</small> | Warp: 3.3 lbs. Fill: 3.3 lbs. |
| Blocking <small>CFFA-4</small> | 1 |
| Cold Crack <small>CFFA-6</small> | -20° F |
| Flex <small>CFFA-10</small> | 30,000 cycles |

Flammability**

| | |
|-----------------|---------|
| CAL TB 117-2013 | Passes |
| NFPA 260 | Class 1 |
| UFAC | Class 1 |

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

** This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

| | |
|---|-----|
| TRIS Free | Yes |
| Low VOC | Yes |
| Recommended Cleaning | |
| Please refer to Detailed Cleaning Instructions. | |

Toll Free **1.800.841.8111**

Visit us at **BurchFabrics.com**