



Repeats Not Shown to Scale.

Velour Onyx 1007511

Meets or exceeds all ACT® Standards

Crypton Seating Fabric
PFAS Free stock may be available



*ACT® Registered Certification Marks

Fabric Specifications

Content	100% Polyester
Finish	Crypton
Backing	Crypton
Weight	20.6 oz. per linear yd
Width	54"
Ends/Picks	Ends: 155 per inch Picks: 30 per inch
Directional	Yes
Railroaded	No
Country of Origin	China

Additional Attributes

PFAS Free	In transition to PFAS Free Sku-Dependent Contact Customer Care
-----------	----------------------------------------------------------------------

Recommended Cleaning

Please refer to Detailed Cleaning Instructions.

Performance Characteristics

Abrasion Resistance	ASTM D4157	100,000 double rubs*
Brush Pill	ASTM D3511	5
Tensile Strength	ASTM D5034	Warp: 499.8 lbs. Fill: 271.2 lbs.
Tear Strength	ASTM D2261	Warp: 10.6 lbs. Fill: 22.6 lbs.
Seam Slippage	ASTM D4034	Warp: 105.7 lbs. Fill: 123.9 lbs.
Colorfastness to Crocking	AATCC 8	Dry: 4.5 Wet: 4.5
Colorfastness to Light	AATCC 16	Hours: 40.0 Class: 4.0

Flammability**

CAL TB 117-2013	Passes
NFPA 260	Class 1
UFAC	Class 1

Although we try hard to make sure colors on our site are accurate, actual colors may vary.
Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

** This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.