
Burch



Meets or exceeds all ACT[®] Standards

Linen Weathered 1007569

Crypton Seating Fabric PFAS Free stock may be available



*ACT[®] Registered Certification Marks

Repeats	Not	Shown	to	Scale
nepears	NUL	3110 MII	ιυ	Scale.

Fabric Specifications

100% Polyester
Crypton
Crypton
17.6 oz. per linear yd
54"
50 yards
Ends: 26 per inch Picks: 25 per inch
Yes
No
China

Additional Attributes

PFAS Free	In transition to PFAS Free
	Sku-Dependent
	Contact Customer Care

Recommended Cleaning

Please refer to Detailed Cleaning Instructions

Performance Characteristics

Abrasion Resistance ASTM D4157	100,000 double rubs*		
Brush Pill ASTM D3511	3		
Tensile Strength ASTM D5034	Warp: 495.4 lbs. Fill: 475.3 lbs.		
Tear Strength ASTM D2261	Warp: 32.0 lbs. Fill: 50.1 lbs.		
Seam Slippage ASTM D4034	Warp: 147.7 lbs. Fill: 173.2 lbs.		
Colorfastness to Crocking AATCC 8	Dry: 4.5 Wet: 4.5		
Colorfastness to Light AATCC 16	Hours: 40.0 Class: 4.0		
Flammability**			
CAL TB 117-2013	Passes		
NFPA 260	Class 1		
UFAC	Class 1		

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

** This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Toll Free 1.800.841.8111

Visit us at BurchFabrics.com