Burch



Repeats Not Shown to Scale

Cityscape Brick 1007583

Meets or exceeds all ACT® Standards

Made in the USA Crypton Seating Fabric Bleach Cleanable



*ACT® Registered Certification Marks

Fabric Specifications

59% Polyester 41% Post Consumer Recycled Polyester
Crypton
Crypton
Yes Ratio: 90% Water / 10% Bleach Solution
18.8 oz. per linear yd
54"
50 yards
Ends: 160 per inch Picks: 107 per inch
H - 7.25 " V - 12.0"
Yes
No
Yes

Performance Characteristics

Abrasion Resistance ASTM D4157	100,000 double rubs*
Brush Pill ASTM D3511	5
Tensile Strength ASTM D5034	Warp: 398.0 lbs. Fill: 372.0 lbs.
Tear Strength ASTM D2262	Warp: 20.0 lbs. Fill: 36.0 lbs.
Seam Slippage ASTM D4034	Warp: 84.0 lbs. Fill: 91.0 lbs.
Colorfastness to Crocking AATCC 8	Dry: 5.0 Wet: 4.5
Colorfastness to Light AATCC 16	Hours: 40.0 Class: 4.0
Flammability**	
CAL TB 117-2013	Passes
NFPA 260	Class 1
UFAC	Class 1

Certifications

Greenguard Gold Certified	Yes - Crypton Technology is Greenguard Gold Certified

Recommended Cleaning

Please refer to Detailed Cleaning Instructions.

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

 $^{{}^{\}star}\, Abrasion \, test \, results \, exceeding \, ACT \, Performance \, Guidelines \, are \, not \, an indicator \, of \, product \, lifespan. \, Multiple \, factors \, affect \, fabric \, durability \, and \, appearance \, retention.$

^{**} This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.