



Repeats Not Shown to Scale.

ESP

### Esprit Dark Aqua 174

Meets or exceeds all ACT® Standards

High Performance Vinyl  
 Bleach Cleanable  
 FR Free – Compliant with CAL AB 2998  
 PFAS Free



\*ACT® Registered Certification Marks

#### Fabric Specifications

|                  |   |
|------------------|---|
| Face             | 100% Vinyl                                    |
| Backing          | 100% Polyester                                |
| Finish/Treatment | Resilience™                                   |
| Bleach Cleanable | Yes<br>Ratio: 90% Water / 10% Bleach Solution |
| Weight           | 30.0 oz. per linear yd                        |
| Thickness        | .97 mm  |
| Width            | 54"   |
| Roll Size        | 30 yards                                      |
| Directional      | No  |
| Railroaded       | No  |

#### Additional Attributes

|   |     |
|---|-----|
| PFAS Free   | Yes |
| Prop 65 Compliant                                 | Yes |
| 16P Phthalate Free                                | Yes |
| Free of Added FR Chemicals / CAL AB2998 Compliant | Yes |
| Free of Added Anti-Bacterial Chemicals            | Yes |
| Antimicrobial                                     | Yes |
| BPA Free  | Yes |
| Free of Conflict Minerals                         | Yes |
| Formaldehyde Free                                 | Yes |
| Free of Heavy Metals                              | Yes |
| Lead Free   | Yes |
| Mildew Resistant                                  | Yes |
| Sulfide Stain Resistant                           | Yes |
| TRIS Free   | Yes |

#### Performance Characteristics

|                                   |                                    |
|-----------------------------------|------------------------------------|
| Abrasion Resistance ASTM D4157    | 250,000 double rubs*               |
| Tensile Strength ASTM D3597-02    | Warp: 95.0 lbs.<br>Fill: 73.0 lbs. |
| Tear Strength CFFA-16             | Warp: 11.9 lbs.<br>Fill: 15.4 lbs. |
| Seam Slippage CFFA-14             | Warp: 67.0 lbs.<br>Fill: 43.0 lbs. |
| Colorfastness to Crocking AATCC 8 | Dry: 5.0<br>Wet: 5.0               |
| UV Resistance CFFA-2              | 500 hours                          |
| Adhesion CFFA-3                   | Warp: 12.5 lbs.<br>Fill: 7.6 lbs.  |
| Blocking CFFA-4                   | 2                                  |
| Cold Crack CFFA-6                 | -20° F                             |
| Flex CFFA-10                      | 25,000 cycles                      |

#### Flammability\*\*

|                          |         |
|--------------------------|---------|
| CAL TB 117-2013          | Passes  |
| NFPA 260                 | Class 1 |
| UFAC                     | Class 1 |
| BIFMA CS-191-53, Sec. 3  | Passes  |
| BIFMA Upholstery, Sec. 4 | Passes  |
| Boston Fire Code         | Passes  |
| IMO 2010 FTP Part 8, 3.1 | Passes  |
| FMVSS 302                | Passes  |

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

\* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

---

**Recommended Cleaning**

---

Please refer to Detailed Cleaning Instructions.

---

\*\* This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

---

Toll Free **1.800.841.8111**

Visit us at **BurchFabrics.com**