50,000 double rubs\*

# Burch



Repeats Not Shown to Scale

# Vintage Lakeshore SVI-103

Meets or exceeds all ACT® Standards

High Performance Vinyl

FR Free - Compliant with CAL AB 2998 PFAS Free



\*ACT® Registered Certification Marks

## **Fabric Specifications**

Face	100% Vinyl
Backing	75% Polyester, 25% Cotton
Finish/Treatment	Standard Acrylic Topcoat
Weight	36.0 oz. per linear yd
Thickness	1.10 mm
Width	54"
Roll Size	30 yards
Directional	Yes
Railroaded	No
Country of Origin	Taiwan

## **Additional Attributes**

PFAS Free	Yes
Prop 65 Compliant	Yes
16P Phthalate Free	Yes
Free of Added FR Chemicals / CAL AB2998 Compliant	Yes
Free of Added Anti-Bacterial Chemicals	Yes
Free of Added Anti-Microbial Chemicals	Yes
BPA Free	Yes
Free of Conflict Minerals	Yes
Formaldehyde Free	Yes
Lead Free	Yes
TRIS Free	Yes

#### **Recommended Cleaning**

Please refer to Detailed Cleaning Instructions.

#### Performance Characteristics

Abrasion Resistance ASTM D4157

Tensile Strength cffA-17	Warp: 67.0 lbs. Fill: 83.0 lbs.
Tear Strength cffA-16	Warp: 5.6 lbs. Fill: 6.2 lbs.
Seam Slippage cffA-14	Warp: 68.0 lbs. Fill: 65.0 lbs.
Colorfastness to Crocking AATCC 8	Dry: 4.5 Wet: 4.0
UV Resistance cffA-2	300 hours
Adhesion cffa-3	Warp: 9.7 lbs. Fill: 9.9 lbs.
Cold Crack CFFA-6	-20° F
Fl	
Flex cffA-10	25,000 cycles
Flammability**	25,000 cycles
	Passes
Flammability**	
Flammability** CAL TB 117-2013	Passes
Flammability**  CAL TB 117-2013  NFPA 260	Passes Class 1
Flammability**  CAL TB 117-2013  NFPA 260  UFAC	Passes Class 1 Class 1
Flammability**  CAL TB 117-2013  NFPA 260  UFAC  ASTM E-84	Passes Class 1 Class 1 Class A or 1
Flammability**  CAL TB 117-2013  NFPA 260  UFAC  ASTM E-84  BIFMA CS-191-53, Sec. 3	Passes Class 1 Class 1 Class A or 1 Passes
Flammability**  CAL TB 117-2013  NFPA 260  UFAC  ASTM E-84  BIFMA CS-191-53, Sec. 3  BIFMA Upholstery, Sec. 4	Passes Class 1 Class 1 Class A or 1 Passes Passes

Vintage is specifically formulated to emulate the appearance of the fine waxed pull-up leather. It is designed to distress and lighten when it is sewn and tufted, stretched or creased. NOTE: Folding the material and keeping it folded over long periods of time in production could result in crease marks that may not come out.

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

- \* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.
- \*\* This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Toll Free 1.800.841.8111

Visit us at BurchFabrics.com