# Burch



Repeats Not Shown to Scale

## Encore Pesto 1008418

Meets or exceeds all ACT® Standards

High Performance Fabric Soil and Stain Repellent PFAS Free stock may be available



\*ACT® Registered Certification Marks

### **Fabric Specifications**

Content 60% Acrylic 40% Polyester  Finish Soil and Stain Repellent  Backing Latex  Weight 20.5 oz. per linear yd  Width 54"  Ends/Picks Ends: 77 per inch Picks: 58 per inch  Directional Yes  Railroaded No  Country of Origin Turkey		
Backing Latex  Weight 20.5 oz. per linear yd  Width 54"  Ends/Picks Ends: 77 per inch Picks: 58 per inch  Directional Yes  Railroaded No	Content	•
Weight 20.5 oz. per linear yd  Width 54**  Ends/Picks Ends: 77 per inch Picks: 58 per inch  Directional Yes  Railroaded No	Finish	Soil and Stain Repellent
Width 54"  Ends/Picks Ends: 77 per inch Picks: 58 per inch  Directional Yes  Railroaded No	Backing	Latex
Ends/Picks Ends: 77 per inch Picks: 58 per inch Directional Yes Railroaded No	Weight	20.5 oz. per linear yd
Picks: 58 per inch  Directional Yes  Railroaded No	Width	54"
Railroaded No	Ends/Picks	
	Directional	Yes
Country of Origin Turkey	Railroaded	No
	Country of Origin	Turkey

#### **Additional Attributes**

PFAS Free	In transition to PFAS Free Sku-Dependent Contact Customer Care
High Performance	Yes
HPD on File	Yes

## **Recommended Cleaning**

Please refer to Detailed Cleaning Instructions.

#### **Performance Characteristics**

Abrasion Resistance ASTM D4157	100,000 double rubs*
Brush Pill ASTM D3511	5
Tensile Strength ASTM D5034	Warp: 163.0 lbs. Fill: 249.0 lbs.
Tear Strength Pending	Warp: 0.0 lbs. Fill: 0.0 lbs.
Seam Slippage ASTM D4034	Warp: 93.4 lbs. Fill: 92.3 lbs.
Colorfastness to Crocking AATCC 8	Dry: 4.5 Wet: 4.5
Colorfastness to Light AATCC 16	Hours: 40.0 Class: 4.5
Flammability**	
CAL TB 117-2013	Passes
NFPA 260	Class 1
UFAC	Class 1

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

- \* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.
- $\star\star$  This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.