



Repeats Not Shown to Scale.

## Bespoke Suiting 1008797

Meets or exceeds all ACT® Standards

High Performance Fabric  
PFAS Free



\*ACT® Registered Certification Marks

### Fabric Specifications

|             |   |
|-------------|---|
| Content     | 70% Wool<br>20% Polyester<br>5% Acrylic<br>5% Nylon |
| Finish      | None  |
| Backing     | None  |
| Weight      | 15.5 oz. per linear yd                              |
| Width       | 54"   |
| Roll Size   | 55 yards  |
| Ends/Picks  | Ends: 37 per inch<br>Picks: 34 per inch             |
| Directional | Yes   |
| Railroaded  | No  |

### Additional Attributes

|                  |     |
|------------------|-----|
| PFAS Free        | Yes |
| High Performance | Yes |
| HPD on File      | Yes |

### Recommended Cleaning\*\*

**WS** - Water-based cleaning agents and foam may be used for cleaning. This fabric may also be cleaned with mild, water-free solvents. Cleaning by a professional cleaning service is recommended.

### Performance Characteristics

|                                   |                                     |
|-----------------------------------|-------------------------------------|
| Abrasion Resistance ASTM D4157    | 100,000 double rubs*                |
| Brush Pill ASTM D3511             | 3                                   |
| Tensile Strength ASTM D5034       | Warp: 108.4 lbs.<br>Fill: 76.2 lbs. |
| Tear Strength ASTM D2261-13       | Warp: 7.8 lbs.<br>Fill: 7.1 lbs.    |
| Seam Slippage ASTM D4034-92       | Warp: 61.1 lbs.<br>Fill: 41.6 lbs.  |
| Colorfastness to Crocking AATCC 8 | Dry: 5.0<br>Wet: 4.0                |
| Colorfastness to Light AATCC 16   | Hours: 40.0<br>Class: 4.0           |

### Flammability\*\*

|                 |         |
|-----------------|---------|
| CAL TB 117-2013 | Passes  |
| NFPA 260        | Class 1 |
| UFAC            | Class 1 |

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

\* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

\*\* This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

\*\* Cleaning information is offered for general guidance and is not a guarantee. The use of certain cleaning agents can be harmful to the surface appearance and lifespan of a product. Burch Fabrics assumes no responsibility for damage to a product resulting from lack of cleaning, improper cleaning or the misuse of cleaning agents. Certain clothing and accessory dyes (such as those used on denim jeans) may migrate to materials and cause permanent damage. Burch Fabrics cannot be held responsible for dye transfer caused by external contaminants.