# Burch



Repeats Not Shown to Scale

# Folio Biscotti 1008968

Meets or exceeds all ACT® Standards

Made in the USA Crypton Seating Fabric PFAS Free stock may be available



\*ACT® Registered Certification Marks

## **Fabric Specifications**

64% Polyester 36% Acrylic
Crypton
Crypton
19.1 oz. per linear yd
54"
55 yards
Ends: 26 per inch Picks: 16 per inch
Yes
No
USA

### **Additional Attributes**

Additional Attributes			
PFAS Free	In transition to PFAS Free Sku-Dependent Contact Customer Care		
Certifications			
Greenguard Gold Certified	Yes - Crypton Technology is Greenguard Gold Certified		
Recommended C	leaning		
Please refer to Detail	ed Cleaning Instructions.		

#### **Performance Characteristics**

Abrasion Resistance ASTM D4157	75,000 double rubs*
Brush Pill ASTM D3511	4
Tensile Strength ASTM D5034	Warp: 325.0 lbs. Fill: 325.0 lbs.
Tear Strength ASTM D2262	Warp: 35.0 lbs. Fill: 35.0 lbs.
Seam Slippage ASTM D4034	Warp: 70.0 lbs. Fill: 70.0 lbs.
Colorfastness to Crocking AATCC 8	Dry: 4.0 Wet: 4.0
Colorfastness to Light AATCC 16	Hours: 40.0 Class: 4.0
Flammability**	
CAL TB 117-2013	Passes
NFPA 260	Class 1
UFAC	Class 1

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

 $\label{product} Final\ determination\ of\ the\ suitability\ of\ this\ product\ for\ an\ application\ rests\ with\ the\ user.$ 

- ${}^{\star}\,\text{Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.}$
- \*\* This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.