# Burch



Repeats Not Shown to Scale

## VALET ADMIRAL 1008990

Meets or exceeds all ACT® Standards

Made in the USA Crypton Seating Fabric PFAS Free stock may be available



\*ACT® Registered Certification Marks

### **Fabric Specifications**

Content	57% Polyester 43% Acrylic	
Finish	Crypton	
Backing	Crypton	
Weight	20.0 oz. per linear yd	
Width	54"	
Roll Size	55 yards	
Ends/Picks	Ends: 26 per inch Picks: 17 per inch	
Directional	Yes	
Railroaded	No	
Country of Origin	USA	

#### Additional Attributes

Additional Attributes		
PFAS Free	In transition to PFAS Free Sku-Dependent Contact Customer Care	
Certifications		
Greenguard Gold Certified	Yes - Crypton Technology is Greenguard Gold Certified	
Recommended C	Cleaning	
Please refer to Detail	ed Cleaning Instructions.	

#### Performance Characteristics

Abrasion Resistance ASTM D4157	50,000 double rubs*
Brush Pill ASTM D3511	4
Tensile Strength ASTM D5034	Warp: 315.0 lbs. Fill: 330.0 lbs.
Tear Strength ASTM D2262	Warp: 45.0 lbs. Fill: 55.0 lbs.
Seam Slippage ASTM D4034	Warp: 60.0 lbs. Fill: 90.0 lbs.
Colorfastness to Crocking AATCC 8	Dry: 4.0 Wet: 4.0
Colorfastness to Light AATCC 16	Hours: 40.0 Class: 4.0
Flammability**	
CAL TB 117-2013	Passes
NFPA 260	Class 1
UFAC	Class 1

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

 $Final\ determination\ of\ the\ suitability\ of\ this\ product\ for\ an\ application\ rests\ with\ the\ user.$ 

- ${\rm *Abrasion\ test\ results\ exceeding\ ACT\ Performance\ Guidelines\ are\ not\ an\ indicator\ of\ product\ lifespan.\ Multiple\ factors\ affect\ fabric\ durability\ and\ appearance\ retention.}$
- \*\* This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.