



Repeats Not Shown to Scale

Chorus Sunset 1009241

Meets or exceeds all ACT® Standards

Made in the USA Crypton Seating Fabric PFAS Free stock may be available



*ACT® Registered Certification Marks

Fabric Specifications

Content	48% Polyester 27% Post Industrial Recycled Polyester 24% Post Consumer Recycled Polyester 1% Nylon
Finish	Crypton
Backing	Crypton
Weight	23.9 oz. per linear yd
Width	54"
Roll Size	50 yards
Ends/Picks	Ends: 160 per inch Picks: 26 per inch
Directional	Yes
Railroaded	No
Country of Origin	USA

Additional Attributes

PFAS Free	In transition to PFAS Free Sku-Dependent Contact Customer Care		
Certifications			
Greenguard Gold Certified	Yes - Crypton Technology is Greenguard Gold Certified		
Recommended Cleaning			
Please refer to Detailed Cleaning Instructions.			

Performance Characteristics

Abrasion Resistance ASTM D4157	75,000 double rubs*		
Brush Pill ASTM D3511	4		
Tensile Strength ASTM D5034	Warp: 255.0 lbs. Fill: 247.0 lbs.		
Tear Strength ASTM D2261	Warp: 50.0 lbs. Fill: 106.0 lbs.		
Seam Slippage ASTM D4034	Warp: 39.0 lbs. Fill: 83.0 lbs.		
Colorfastness to Crocking AATCC 8	Dry: 4.0 Wet: 3.0		
Colorfastness to Light AATCC 16	Hours: 40.0 Class: 4.0		
Flammability**			
CAL TB 117-2013	Passes		
NFPA 260	Class 1		
UFAC	Class 1		

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

 $\label{product} Final\ determination\ of\ the\ suitability\ of\ this\ product\ for\ an\ application\ rests\ with\ the\ user.$

- ${}^{\star}\,\text{Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.}$
- ** This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.