
Burch



Silvertex Neutra STX-8830

Meets or exceeds all ACT[®] Standards

High Performance Vinyl Bleach Cleanable Indoor/Outdoor FR Free – Compliant with CAL AB 2998 PFAS Free



Repeats Not Shown to Scale.

Fabric Specifications

Face	100% Vinyl	
Backing	Hi-Loft2 [™] 100% Polyester	
Finish/Treatment	Permablok ^{3®} Silverguard [®]	
Bleach Cleanable	Yes Ratio: 75% Water / 25% Bleach Solution	
Indoor/Outdoor	Yes	
Weight	30.0 oz. per linear yd	
Thickness	1.14 mm	
Width	54"	
Roll Size	30 yards	
Directional	Yes	
Railroaded	No	
Country of Origin	Colombia	

Additional Attributes

PFAS Free	Yes
Prop 65 Compliant	Yes
Free of Added FR Chemicals / CAL AB2998 Compliant	Yes
Free of Added Anti-Bacterial Chemicals	Yes
Free of Added Anti-Microbial Chemicals	Yes
BPA Free	Yes
Free of Conflict Minerals	Yes
Formaldehyde Free	Yes
Free of Heavy Metals	Yes
Lead Free	Yes
Mildew Resistant	Yes
Sulfide Stain Resistant	Yes

Performance Characteristics

Abrasion Resistance ASTM D4157	100,000 double rubs*
Tensile Strength CFFA-17	Warp: 123.0 lbs. Fill: 87.0 lbs.
Tear Strength CFFA-16	Warp: 20.0 lbs. Fill: 20.0 lbs.
Seam Slippage DIN 54301	Warp: 12.0 lbs. Fill: 9.2 lbs.
Colorfastness to Crocking CFFA-7	Dry: Excellent Wet: Excellent
UV Resistance AATCC TM 16E	1000 hours
Adhesion CFFA-3	Warp: 3.3 lbs. Fill: 3.3 lbs.
Cold Crack CFFA-6	-10° F
Flammability**	
CAL TB 117-2013	Passes
NFPA 260	Class 1
UFAC	Class 1
BIFMA X5.7	Class A & 1
Boston Fire Code	Passes
Federal Aviation Specification	Passes
Federal Specification	Passes
IMO 2010 FTP Part 8, 3.1 & 3.2	Passes
FMVSS 302	Passes
Port Authority of NY/NJ	Passes

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

Yes

Recommended Cleaning

Please refer to Detailed Cleaning Instructions.

** This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Toll Free 1.800.841.8111

Visit us at BurchFabrics.com