# Burch



Repeats Not Shown to Scale

## Allante Burgundy 832

Meets or exceeds all ACT® Standards

High Performance Vinyl

Indoor/Outdoor FR Free – Compliant with CAL AB 2998 PFAS Free



\*ACT® Registered Certification Marks

#### **Fabric Specifications**

Face 100% Vinyl  Backing 100% Polyester  Finish/Treatment Stain Resistant Finish  Indoor/Outdoor Yes  Weight 29.25 oz. per linear yd  Thickness 1.14 mm  Width 54"  Roll Size 40 yards  Directional No  Railroaded No  Country of Origin Canada		
Finish/Treatment Stain Resistant Finish Indoor/Outdoor Yes Weight 29.25 oz. per linear yd Thickness 1.14 mm Width 54" Roll Size 40 yards Directional No Railroaded No	Face	100% Vinyl
Indoor/Outdoor Yes  Weight 29.25 oz. per linear yd  Thickness 1.14 mm  Width 54"  Roll Size 40 yards  Directional No  Railroaded No	Backing	100% Polyester
Weight 29.25 oz. per linear yd  Thickness 1.14 mm  Width 54"  Roll Size 40 yards  Directional No  Railroaded No	Finish/Treatment	Stain Resistant Finish
Thickness 1.14 mm  Width 54"  Roll Size 40 yards  Directional No  Railroaded No	Indoor/Outdoor	Yes
Width 54"  Roll Size 40 yards  Directional No  Railroaded No	Weight	29.25 oz. per linear yd
Roll Size 40 yards  Directional No  Railroaded No	Thickness	1.14 mm
Directional No Railroaded No	Width	54"
Railroaded No	Roll Size	40 yards
	Directional	No
Country of Origin Canada	Railroaded	No
	Country of Origin	Canada

### **Additional Attributes**

PFAS Free	Yes
16P Phthalate Free	Yes
Free of Added FR Chemicals / CAL AB2998 Compliant	Yes
Free of Added Anti-Bacterial Chemicals	Yes
Free of Added Anti-Microbial Chemicals	Yes
BPA Free	Yes
Free of Conflict Minerals	Yes
Formaldehyde Free	Yes
Free of Heavy Metals	Yes
Lead Free	Yes
Mildew Resistant	Yes
Sulfide Stain Resistant	Yes
TRIS Free	Yes
Low VOC	Yes

#### Performance Characteristics

Abrasion Resistance ASTM D4157	100,000 double rubs*
Tensile Strength ASTM D751	Warp: 95.0 lbs. Fill: 68.0 lbs.
Tear Strength ASTM D1117	Warp: 23.0 lbs. Fill: 27.0 lbs.
Colorfastness to Crocking Fed Std 191A-5651	Dry: Good Wet: Good
UV Resistance ASTM G153-00a	1000 hours
Adhesion cffA-3	Warp: 3.5 lbs. Fill: 3.5 lbs.
Blocking cffA-4	2
Cold Crack CFFA-6	-25° F
Flex ASTM D2097-03	30,000 cycles
Flammability**	
CAL TB 117-2013	Passes
NFPA 260	Class 1
UFAC	Class 1
FMVSS 302	Passes

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

 $Final\ determination\ of\ the\ suitability\ of\ this\ product\ for\ an\ application\ rests\ with\ the\ user.$ 

Proposition 65 Warning: Yes

- \* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.
- \*\* This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Recommen	ded Cleaning
Please refer to	Detailed Cleaning Instructions.

Toll Free **1.800.841.8111** 

Visit us at **BurchFabrics.com**