
Burch

Technical Details



Repeats Not Shown to Scale.

ALLANTE CHARCOAL

AL

804

Meets or exceeds all ACT® Standards

High Performance Vinyl
Indoor/Outdoor
FR Free - Compliant with CAL AB 2998
PFAS Free
CFFA-HC-201 Compliant

*ACT® Registered Certification Marks

Fabric Specifications

Face	100% Vinyl
Backing	100% Polyester
Finish/Treatment	Stain Resistant Finish
Indoor/Outdoor	Yes
Weight	29.25 oz. per linear yd
Thickness	1.14 mm
Width	54"
Roll Size	40 yards
Directional	No
Railroaded	No
Country of Origin	Canada

Additional Attributes

PFAS Free	Yes
CFFA-HC-201 Compliant	Yes
16P Phthalate Free	Yes
Free of Added FR Chemicals / CAL AB2998 Compliant	Yes
Free of Added Anti-Bacterial Chemicals	Yes
Free of Added Anti-Microbial Chemicals	Yes
BPA Free	Yes
Free of Conflict Minerals	Yes
Formaldehyde Free	Yes
Free of Heavy Metals	Yes
Lead Free	Yes
Mildew Resistant	Yes
Sulfide Stain Resistant	Yes
TRIS Free	Yes

Performance Characteristics

Abrasion Resistance ASTM D4157	100,000 double rubs*
Tensile Strength ASTM D751	Warp: 95.0 lbs. Fill: 68.0 lbs.
Tear Strength ASTM D1117	Warp: 23.0 lbs. Fill: 27.0 lbs.
Colorfastness to Crocking Fed Std 191A-5651	Dry: Good Wet: Good
UV Resistance ASTM G153-00a	1000 hours
Adhesion CFFA-3	Warp: 3.5 lbs. Fill: 3.5 lbs.
Blocking CFFA-4	2
Cold Crack CFFA-6	-25° F
Flex ASTM D2097-03	30,000 cycles

Flammability**

CAL TB 117-2013	Passes
NFPA 260	Class 1
UFAC	Class 1
FMVSS 302	Passes

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

Proposition 65 Warning: Yes

* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

** This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Low VOC	Yes

Recommended Cleaning

Please refer to Detailed Cleaning Instructions.