



Repeats Not Shown to Scale.

AL  
Allante Galaxy 818

Meets or exceeds all ACT® Standards

High Performance Vinyl

Indoor/Outdoor  
FR Free – Compliant with CAL AB 2998  
PFAS Free



\*ACT® Registered Certification Marks

Fabric Specifications

|                   |                         |
|-------------------|-------------------------|
| Face              | 100% Vinyl              |
| Backing           | 100% Polyester          |
| Finish/Treatment  | Stain Resistant Finish  |
| Indoor/Outdoor    | Yes                     |
| Weight            | 29.25 oz. per linear yd |
| Thickness         | 1.14 mm                 |
| Width             | 54"                     |
| Roll Size         | 40 yards                |
| Directional       | No                      |
| Railroaded        | No                      |
| Country of Origin | Canada                  |

Additional Attributes

|   |     |
|---|-----|
| PFAS Free   | Yes |
| 16P Phthalate Free                                | Yes |
| Free of Added FR Chemicals / CAL AB2998 Compliant | Yes |
| Free of Added Anti-Bacterial Chemicals            | Yes |
| Free of Added Anti-Microbial Chemicals            | Yes |
| BPA Free  | Yes |
| Free of Conflict Minerals                         | Yes |
| Formaldehyde Free                                 | Yes |
| Free of Heavy Metals                              | Yes |
| Lead Free   | Yes |
| Mildew Resistant                                  | Yes |
| Sulfide Stain Resistant                           | Yes |
| TRIS Free   | Yes |
| Low VOC   | Yes |

Performance Characteristics

|   |                                    |
|---|------------------------------------|
| Abrasion Resistance ASTM D4157              | 100,000 double rubs*               |
| Tensile Strength ASTM D751                  | Warp: 95.0 lbs.<br>Fill: 68.0 lbs. |
| Tear Strength ASTM D1117                    | Warp: 23.0 lbs.<br>Fill: 27.0 lbs. |
| Colorfastness to Crocking Fed Std 191A-5651 | Dry: Good<br>Wet: Good             |
| UV Resistance ASTM G153-00a                 | 1000 hours                         |
| Adhesion CFFA-3                             | Warp: 3.5 lbs.<br>Fill: 3.5 lbs.   |
| Blocking CFFA-4                             | 2                                  |
| Cold Crack CFFA-6                           | -25° F                             |
| Flex ASTM D2097-03                          | 30,000 cycles                      |

Flammability\*\*

|                 |         |
|-----------------|---------|
| CAL TB 117-2013 | Passes  |
| NFPA 260        | Class 1 |
| UFAC            | Class 1 |
| FMVSS 302       | Passes  |

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

Proposition 65 Warning: Yes

\* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

\*\* This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

---

**Recommended Cleaning**

---

Please refer to Detailed Cleaning Instructions.

---

---

Toll Free **1.800.841.8111**

Visit us at **BurchFabrics.com**