
Burch

Technical Details



Repeats Not Shown to Scale.

FLICKER RUBY

1009429

Meets or exceeds all ACT® Standards

PVC Free Polyurethane
Ink Cleanable
Denim Dye Cleanable
Bleach Cleanable
FR Free - Compliant with CAL AB 2998
PFAS Free
CFFA-HC-201 Compliant

*ACT® Registered Certification Marks

Fabric Specifications

Face	100% PVC Free Polyurethane
Backing	75% Polyester, 25% Cotton
Finish/Treatment	Writer's Block™ Ink Resistant Technology
Bleach Cleanable	Yes Ratio: 80% Water / 20% Bleach Solution
Weight	20.0 oz. per linear yd
Thickness	1.00 mm
Width	54"
Roll Size	30 yards
Directional	No
Railroaded	No
Country of Origin	China

Additional Attributes

Ink Cleanable	Yes
Denim Dye Cleanable	Yes
PFAS Free	Yes
CFFA-HC-201 Compliant	Yes
PVC Free	Yes
Prop 65 Compliant	Yes
16P Phthalate Free	Yes
Free of Added FR Chemicals / CAL AB2998 Compliant	Yes
Free of Added Anti-Bacterial Chemicals	Yes
Free of Added Anti-Microbial Chemicals	Yes
BPA Free	Yes
Free of Conflict Minerals	Yes
Formaldehyde Free	Yes

Performance Characteristics

Abrasion Resistance ASTM D4157	165,000 double rubs*
Tensile Strength CFFA-17	Warp: 128.0 lbs. Fill: 106.0 lbs.
Tear Strength CFFA-16c	Warp: 11.3 lbs. Fill: 7.6 lbs.
Seam Slippage DIN 54301	Warp: 88.7 lbs. Fill: 87.9 lbs.
Colorfastness to Crocking AATCC 8	Dry: 5.0 Wet: 5.0
UV Resistance ASTM D4329 QUV	200 hours
Adhesion CFFA-3	Warp: 10.1 lbs. Fill: 6.8 lbs.
Blocking CFFA-4	1
Cold Crack CFFA-6a	-20° F
Flex CFFA-10	25,000 cycles
Hydrolysis	7 Weeks

Flammability**

CAL TB 117-2013	Passes
NFPA 260	Class 1
UFAC	Class 1
IMO 2010 FTP Part 8, 3.1	Passes
FMVSS 302	Passes

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

The use of polyurethane for welt cord in upholstery applications is strongly discouraged. Even though Burch's polyurethane products are designed to exceed industry abrasion standards, when used with welt cord the exposed material becomes more vulnerable to abrasion and may experience

Final determination of the suitability of this product for an application rests with the user.

* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

Lead Free	Yes
Mildew Resistant	Yes
Sulfide Stain Resistant	Yes
TRIS Free	Yes
Low VOC	Yes

Recommended Cleaning

Please refer to Detailed Cleaning Instructions.

** This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.