
Burch



Repeats Not Shown to Scale

Carrara Black

CR

500

Meets or exceeds all ACT® Standards

High Performance Vinyl

Indoor/Outdoor PFAS Free



*ACT® Registered Certification Marks

Fabric Specifications

Face	100% Vinyl
Backing	100% Polyester
Finish/Treatment	Stain Resistant Finish
Indoor/Outdoor	Yes
Weight	29.25 oz. per linear yd
Thickness	1.14 mm
Width	54"
Roll Size	40 yards
Directional	Yes
Railroaded	No
Country of Origin	Canada

Additional Attributes

Recommended Cleaning

PFAS Free	Yes
16P Phthalate Free	Yes
Antibacterial	Yes
Antimicrobial	Yes
BPA Free	Yes
Free of Conflict Minerals	Yes
Formaldehyde Free	Yes
Free of Heavy Metals	Yes
Lead Free	Yes
Mildew Resistant	Yes
Sulfide Stain Resistant	Yes
TRIS Free	Yes
Low VOC	Yes

Performance Characteristics

Abrasion Resistance ASTM D4157	100,000 double rubs*
Tensile Strength CFFA-17	Warp: 95.0 lbs. Fill: 68.0 lbs.
Tear Strength ASTM D1117	Warp: 23.0 lbs. Fill: 27.0 lbs.
Colorfastness to Crocking Fed Std 191A-5651	Dry: Good Wet: Good
UV Resistance ASTM G153-04	1000 hours
Adhesion CFFA-3	Warp: 3.5 lbs. Fill: 3.5 lbs.
Blocking cffA-4	2
Cold Crack CFFA-6	-25° F
Flex ASTM D2097-03	30,000 cycles
Flammability**	
CAL TB 117-2013	Passes
NFPA 260	Class 1
UFAC	Class 1
FMVSS 302	Passes

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

 $Final\ determination\ of\ the\ suitability\ of\ this\ product\ for\ an\ application\ rests\ with\ the\ user.$

Proposition 65 Warning: Yes

- * Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.
- ** This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Please refer to Detailed Cleaning Instructions.	

Toll Free **1.800.841.8111**

Visit us at **BurchFabrics.com**