



Repeats Not Shown to Scale.

Nimbus Flame 1009671

Meets or exceeds all ACT® Standards

Made in the USA
High Performance Fabric
Soil and Stain Repellent



*ACT® Registered Certification Marks

Fabric Specifications

Content	25% Rayon 24% Polyester 21% Post Consumer Recycled Polyester 20% Nylon 10% Post Industrial Recycled Polyester
Finish	Soil and Stain Repellent
Backing	Acrylic
Weight	16.0 oz. per linear yd
Width	54"
Roll Size	60 yards
Ends/Picks	Ends: 77 per inch Picks: 178 per inch
Repeat	H - 13.75 " V - 18.0"
Directional	Yes
Railroaded	No
Made in the USA	Yes

Performance Characteristics

Abrasion Resistance	ASTM D4157	60,000 double rubs*
Brush Pill	BRUSH + SPONGE	3
Tensile Strength	ASTM D5034	Warp: 205.0 lbs. Fill: 204.0 lbs.
Tear Strength	ASTM D2261	Warp: 57.0 lbs. Fill: 39.0 lbs.
Seam Slippage	ASTM D4034	Warp: 62.0 lbs. Fill: 89.0 lbs.
Colorfastness to Crocking	AATCC 8	Dry: 4.0 Wet: 4.0
Colorfastness to Light	AATCC 16	Hours: 40.0 Class: 4.0

Flammability**

CAL TB 117-2013	Passes
NFPA 260	Class 1
UFAC	Class 1

Additional Attributes

High Performance	Yes
------------------	-----

Recommended Cleaning

Please refer to Detailed Cleaning Instructions.

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

** This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

1-800-841-8111

Visit us at BurchFabrics.com