



Repeats Not Shown to Scale.

### Woolen Hydro 1009846

Meets or exceeds all ACT® Standards

High Performance Fabric



\*ACT® Registered Certification Marks

#### Fabric Specifications

Content	70% Wool 20% Polyester 5% Acrylic 5% Nylon
Finish	None
Backing	None
Weight	10.0 oz. per linear yd
Width	54"
Roll Size	50 yards
Ends/Picks	Ends: 38 per inch Picks: 35 per inch
Directional	Yes
Railroaded	No

#### Additional Attributes

High Performance	Yes
HPD on File	Yes

#### Recommended Cleaning

Please refer to Detailed Cleaning Instructions.

#### Performance Characteristics

Abrasion Resistance ASTM D4966	75,000 double rubs*
Brush Pill ASTM D3511	3
Tensile Strength ASTM D5034	Warp: 108.3 lbs. Fill: 57.4 lbs.
Tear Strength ASTM D2261	Warp: 11.8 lbs. Fill: 7.0 lbs.
Seam Slippage ASTM D4034	Warp: 86.9 lbs. Fill: 56.0 lbs.
Colorfastness to Crocking AATCC 8	Dry: 5.0 Wet: 5.0
Colorfastness to Light AATCC 16	Hours: 40.0 Class: 5.0

#### Flammability\*\*

CAL TB 117-2013	Passes
NFPA 260	Class 1
UFAC	Class 1

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

\* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

\*\* This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.