



Repeats Not Shown to Scale.

### Sketch Twilight 1011093

Meets or exceeds all ACT® Standards

High Performance Vinyl  
 Ink Cleanable  
 Denim Dye Cleanable  
 Bleach Cleanable



\*ACT® Registered Certification Marks

#### Fabric Specifications

|                  |   |
|------------------|---|
| Face             | 100% Vinyl                                    |
| Backing          | 65% Polyester,<br>35% Cotton                  |
| Finish/Treatment | Forbid SRT™                                   |
| Bleach Cleanable | Yes<br>Ratio: 90% Water / 10% Bleach Solution |
| Weight           | 30.0 oz. per linear yd                        |
| Thickness        | 1.00 mm                                       |
| Width            | 54"   |
| Roll Size        | 30 yards                                      |
| Directional      | Yes   |
| Railroaded       | No  |

#### Additional Attributes

|                           |     |
|---------------------------|-----|
| Ink Cleanable             | Yes |
| Denim Dye Cleanable       | Yes |
| 16P Phthalate Free        | Yes |
| Antibacterial             | Yes |
| Antimicrobial             | Yes |
| BPA Free                  | Yes |
| Free of Conflict Minerals | Yes |
| Formaldehyde Free         | Yes |
| Free of Heavy Metals      | Yes |
| Lead Free                 | Yes |
| Mildew Resistant          | Yes |
| Sulfide Stain Resistant   | Yes |
| TRIS Free                 | Yes |
| Low VOC                   | Yes |

#### Performance Characteristics

|  |                                     |
|--|-------------------------------------|
| Abrasion Resistance <small>ASTM D4157</small>    | 100,000 double rubs*                |
| Tensile Strength <small>ASTM D751</small>        | Warp: 80.0 lbs.<br>Fill: 120.0 lbs. |
| Tear Strength <small>ASTM D751</small>           | Warp: 10.0 lbs.<br>Fill: 15.0 lbs.  |
| Colorfastness to Crocking <small>AATCC 8</small> | Dry: 4.0<br>Wet: 4.0                |
| UV Resistance <small>ASTM G154</small>           | 300 hours                           |
| Adhesion <small>CFFA-3</small>                   | Warp: 4.0 lbs.<br>Fill: 4.0 lbs.    |
| Cold Crack <small>CFFA-6</small>                 | -10° F                              |

#### Flammability\*\*

|                 |         |
|-----------------|---------|
| CAL TB 117-2013 | Passes  |
| NFPA 260        | Class 1 |
| UFAC            | Class 1 |
| FMVSS 302       | Passes  |

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

Proposition 65 Warning: Yes

\* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

\*\* This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

---

**Recommended Cleaning**

---

Please refer to Detailed Cleaning Instructions.

---

---

Toll Free **1.800.841.8111**

Visit us at **BurchFabrics.com**