Burch



Repeats Not Shown to Scale

Halo Mink 1011005

Meets or exceeds all ACT® Standards

Crypton Seating Fabric PFAS Free stock may be available



*ACT® Registered Certification Marks

Fabric Specifications

Content	55% Polyester 38% Acrylic 7% Viscose	
Finish	Crypton	
Backing	Crypton	
Weight	21.7 oz. per linear yd	
Width	54"	
Roll Size	55 yards	
Ends/Picks	Ends: 167 per inch Picks: 53 per inch	
Repeat	H - 7.1 " V - 5.6 "	
Directional	Yes	
Railroaded	No	
Country of Origin	Turkey	

Additional Attributes

PFAS Free	In transition to PFAS Free Sku-Dependent	
	Contact Customer Care	
Certifications		
Greenguard Gold Certified	Yes - Crypton Technology is Greenguard Gold Certified	
Recommended Cleaning		
Please refer to Natailed Cleaning Instructions		

Performance Characteristics

Abrasion Resistance ASTM D4157	50,000 double rubs*	
Brush Pill ASTM D3511	4.5	
Tensile Strength ASTM D5034	Warp: 298.6 lbs. Fill: 115.5 lbs.	
Tear Strength ASTM D2261	Warp: 26.4 lbs. Fill: 47.9 lbs.	
Seam Slippage ASTM D4034	Warp: 87.3 lbs. Fill: 95.2 lbs.	
Colorfastness to Crocking AATCC 8	Dry: 4.5 Wet: 4.5	
Colorfastness to Light AATCC 16	Hours: 40.0 Class: 4.0	
Flammability**		
CAL TB 117-2013	Passes	
NFPA 260	Class 1	
UFAC	Class 1	

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

 $\label{product} Final\ determination\ of\ the\ suitability\ of\ this\ product\ for\ an\ application\ rests\ with\ the\ user.$

- ${\rm *Abrasion\ test\ results\ exceeding\ ACT\ Performance\ Guidelines\ are\ not\ an\ indicator\ of\ product\ lifespan.\ Multiple\ factors\ affect\ fabric\ durability\ and\ appearance\ retention.}$
- ** This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.