Burch



Repeats Not Shown to Scale.

High Line Maple 1011154

Meets or exceeds all ACT® Standards

Crypton Seating Fabric Bleach Cleanable PFAS Free



*ACT® Registered Certification Marks

Fabric Specifications

100% Polyester
Crypton
Crypton
Yes Ratio: 90% Water / 10% Bleach Solution
21.2 oz. per linear yd
54"
50 yards
Ends: 150 per inch Picks: 42 per inch
Yes
Yes
China

Additional Attributes

PFAS Free	Yes
Certifications	
Greenguard Gold Certified	Yes - Crypton Technology is Greenguard Gold Certified
Recommended C	

Performance Characteristics

Abrasion Resistance ASTM D4157	100,000 double rubs*
Brush Pill ASTM D3511	5
Tensile Strength ASTM D5034	Warp: 294.0 lbs. Fill: 157.7 lbs.
Tear Strength ASTM D2262	Warp: 25.5 lbs. Fill: 23.3 lbs.
Seam Slippage ASTM D4034	Warp: 93.6 lbs. Fill: 83.5 lbs.
Colorfastness to Crocking AATCC 8	Dry: 4.5 Wet: 4.5
Colorfastness to Light AATCC 16	Hours: 40.0 Class: 4.0
Flammability**	
CAL TB 117-2013	Passes
NFPA 260	Class 1
UFAC	Class 1

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

 $\label{product} Final\ determination\ of\ the\ suitability\ of\ this\ product\ for\ an\ application\ rests\ with\ the\ user.$

- * Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.
- ** This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Please refer to Detailed Cleaning Instructions.