# Burch



Repeats Not Shown to Scale

## **Dynasty Weathered Taupe** 1011077

Meets or exceeds all ACT® Standards

Made in the USA Nanotex Seating Fabric Bleach Cleanable PFAS Free stock may be available



\*ACT® Registered Certification Marks

### **Fabric Specifications**

Content 100% Polyester  Finish Nanotex  Backing Acrylic  Bleach Cleanable Yes Ratio: 90% Water / 10% Bleach Solution  Weight 24.1 oz. per linear yd  Width 54"  Roll Size 60 yards  Ends/Picks Ends: 160 per inch Picks: 63 per inch  Repeat H - 30.13 " V - 24.76 "
Backing Acrylic  Bleach Cleanable Yes Ratio: 90% Water / 10% Bleach Solution  Weight 24.1 oz. per linear yd  Width 54"  Roll Size 60 yards  Ends: 160 per inch Picks: 63 per inch  Repeat H - 30.13 "
Bleach Cleanable Yes Ratio: 90% Water / 10% Bleach Solution  Weight 24.1 oz. per linear yd  Width 54"  Roll Size 60 yards  Ends/Picks Ends: 160 per inch Picks: 63 per inch  Repeat H - 30.13 "
Ratio: 90% Water / 10% Bleach Solution  Weight 24.1 oz. per linear yd  Width 54"  Roll Size 60 yards  Ends/Picks Ends: 160 per inch Picks: 63 per inch  Repeat H - 30.13 "
Width         54"           Roll Size         60 yards           Ends/Picks         Ends: 160 per inch Picks: 63 per inch           Repeat         H - 30.13 "
Roll Size 60 yards  Ends/Picks Ends: 160 per inch Picks: 63 per inch  Repeat H - 30.13 "
Ends/Picks Ends: 160 per inch Picks: 63 per inch  Repeat H - 30.13 "
Picks: 63 per inch  Repeat H - 30.13 "
Directional Yes
Railroaded No
Country of Origin USA

#### **Additional Attributes**

PFAS Free	In transition to PFAS Free Sku-Dependent Contact Customer Care	
High Performance Yes		
HPD on File	Yes	
Recommended Cleaning		
Please refer to Detailed Cleaning Instructions.		

#### **Performance Characteristics**

Abrasion Resistance ASTM D4157	63,000 double rubs*	
Brush Pill ASTM D3511	4	
Tensile Strength ASTM D5034	Warp: 460.0 lbs. Fill: 460.0 lbs.	
Tear Strength ASTM D2261	Warp: 41.0 lbs. Fill: 75.0 lbs.	
Seam Slippage ASTM D4034	Warp: 96.0 lbs. Fill: 110.0 lbs.	
Colorfastness to Crocking AATCC 8	Dry: 4.0 Wet: 3.0	
Colorfastness to Light AATCC 16	Hours: 40.0 Class: 4.0	
Flammability**		
CAL TB 117-2013	Passes	
NFPA 260	Class 1	
UFAC	Class 1	

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

 $\label{thm:continuous} Final\ determination\ of\ the\ suitability\ of\ this\ product\ for\ an\ application\ rests\ with\ the\ user.$ 

- ${}^{\star}\,\text{Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.}$
- \*\* This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.