# Burch



Repeats Not Shown to Scale

## Wayfarer Marble 1011225

Meets or exceeds all ACT® Standards

Crypton Seating Fabric PFAS Free stock may be available



\*ACT® Registered Certification Marks

### **Fabric Specifications**

Content	68% Polyester 29% Viscose 3% Cotton
Finish	Crypton
Backing	Crypton
Weight	23.5 oz. per linear yd
Width	54"
Roll Size	50 yards
Ends/Picks	Ends: 92 per inch Picks: 20 per inch
Directional	Yes
Railroaded	No
Country of Origin	India

### **Additional Attributes**

PFAS Free	In transition to PFAS Free Sku-Dependent	
	Contact Customer Care	
Certifications		
Greenguard Gold Certified	Yes - Crypton Technology is Greenguard Gold Certified	
Recommended Cleaning		
Please refer to Details	ed Cleaning Instructions.	

#### **Performance Characteristics**

Abrasion Resistance ASTM D4157	100,000 double rubs*	
Brush Pill ASTM D3511	3	
Tensile Strength ASTM D5034	Warp: 259.2 lbs. Fill: 126.2 lbs.	
Tear Strength ASTM D2262	Warp: 35.8 lbs. Fill: 63.0 lbs.	
Seam Slippage ASTM D4034	Warp: 99.9 lbs. Fill: 37.3 lbs.	
Colorfastness to Crocking AATCC 8	Dry: 4.0 Wet: 4.0	
Colorfastness to Light AATCC 16	Hours: 40.0 Class: 4.0	
Flammability**		
CAL TB 117-2013	Passes	
NFPA 260	Class 1	
UFAC	Class 1	

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

 $Final\ determination\ of\ the\ suitability\ of\ this\ product\ for\ an\ application\ rests\ with\ the\ user.$ 

- ${}^{\star}\,\text{Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.}$
- \*\* This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.