
# Burch



Repeats Not Shown to Scale.

## **Boucle Buttercup** 1011252

Meets or exceeds all ACT® Standards

High Performance Vinyl Denim Dye Cleanable Bleach Cleanable FR Free – Compliant with CAL AB 2998 PFAS Free CFFA-HC-201 Compliant



\*ACT® Registered Certification Marks

### **Fabric Specifications**

Backing 100% Polyester  Finish/Treatment Resilience™  Bleach Cleanable Yes Ratio: 80% Water / 20% Bleach Solution  Weight 31.0 oz. per linear yd  Thickness 1.20 mm  Width 54"  Roll Size 30 yards  Directional Yes	Face	100% Vinyl
Bleach Cleanable Yes Ratio: 80% Water / 20% Bleach Solution  Weight 31.0 oz. per linear yd  Thickness 1.20 mm  Width 54"  Roll Size 30 yards	Backing	100% Polyester
Ratio: 80% Water / 20% Bleach Solution  Weight 31.0 oz. per linear yd  Thickness 1.20 mm  Width 54"  Roll Size 30 yards	Finish/Treatment	Resilience™
Thickness 1.20 mm  Width 54"  Roll Size 30 yards	Bleach Cleanable	
Width 54"  Roll Size 30 yards	Weight	31.0 oz. per linear yd
Roll Size 30 yards	Thickness	1.20 mm
	Width	54"
Directional Yes	Roll Size	30 yards
	Directional	Yes
Railroaded No	Railroaded	No
Country of Origin Taiwan	Country of Origin	Taiwan

#### **Additional Attributes**

Denim Dye Cleanable	Yes
PFAS Free	Yes
CFFA-HC-201 Compliant	Yes
Prop 65 Compliant	Yes
16P Phthalate Free	Yes
Free of Added FR Chemicals / CAL AB2998 Compliant	Yes
BPA Free	Yes
Free of Conflict Minerals	Yes
Formaldehyde Free	Yes
Free of Heavy Metals	Yes
Lead Free	Yes
Sulfide Stain Resistant	Yes
TRIS Free	Yes

#### **Performance Characteristics**

Abrasion Resistance ASTM D4157	250,000 double rubs*
Tensile Strength ASTM D751-06	Warp: 95.0 lbs. Fill: 73.0 lbs.
	1 111. 7 3.0 103.
Tear Strength CFFA-16	Warp: 7.2 lbs.
	Fill: 11.0 lbs.
Seam Slippage ASTM D751-06	Warp: 48.0 lbs.
11 3	Fill: 40.0 lbs.
Colorfastness to Crocking AATCC 8	Dry: 5.0
Coloriastiless to crocking AATCC 8	Wet: 5.0
	WCL 0.0
UV Resistance CFFA-2	300 hours
Adhesion ASTM D751-06	Warp: 8.0 lbs.
7.4.100.017 / 101.100	Fill: 8.1 lbs.
DI II	
Blocking cffA-4	1
Cold Crack cffA-6	-20° F
Flex CFFA-10	25,000 cycles
Flammability**	
CAL TB 117-2013	Passes
NFPA 260	Class 1
UFAC	Class 1

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

- \* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.
- \*\* This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

HPD on File	Yes
Recommended Cleaning	
Please refer to Detailed Cleaning Instructions.	

Toll Free **1.800.841.8111** 

Visit us at BurchFabrics.com