# Burch



Repeats Not Shown to Scale.

## **BILLIARD IRON**

1011700

Meets or exceeds all ACT® Standards

Supreen Moisture Barrier Bleach Cleanable PFAS Free



\*ACT® Registered Certification Marks

#### **Fabric Specifications**

Content	88% Polyester 10% Polyurethane 2% Silicone
Finish	Supreen
Backing	Supreen Moisture Barrier
Bleach Cleanable	Yes Ratio: 90% Water / 10% Bleach Solution
Weight	15.5 oz. per linear yd
Width	54"
Roll Size	45 yards
Ends/Picks	Ends: 25.4 per inch Picks: 23.6 per inch
Directional	Yes
Railroaded	No
Country of Origin	China

### **Additional Attributes**

PFAS Free	Yes	
Supreen	Yes	
Recommended Cleaning		
Please refer to Detailed Cleaning Instructions.		

#### **Performance Characteristics**

Abrasion Resistance ASTM D4157	100,000 double rubs*
Brush Pill ASTM D3511	5
Tensile Strength ASTM D5034	Warp: 215.0 lbs. Fill: 170.0 lbs.
Tear Strength ASTM D2261	Warp: 27.3 lbs. Fill: 24.0 lbs.
Seam Slippage ASTM D4034	Warp: 87.0 lbs. Fill: 93.0 lbs.
Colorfastness to Crocking AATCC 8	Dry: 5.0 Wet: 5.0
Colorfastness to Light AATCC 16	Hours: 40.0 Class: 5.0
Flammability**	
CAL TB 117-2013	Passes
NFPA 260	Class 1
UFAC	Class 1

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

 $Final\ determination\ of\ the\ suitability\ of\ this\ product\ for\ an\ application\ rests\ with\ the\ user.$ 

- ${}^{\star}\,\text{Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.}$
- $\star\star$  This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.