Burch



Repeats Not Shown to Scale

Triton Depth 1011602

Meets or exceeds all ACT® Standards

Made in the USA Crypton Seating Fabric Bleach Cleanable PFAS Free stock may be available



*ACT® Registered Certification Marks

Fabric Specifications

Content	76% Polyester 24% Seaqual	
Finish	Crypton	
Backing	Crypton	
Bleach Cleanable	Yes Ratio: 90% Water / 10% Bleach Solution	
Weight	18.3 oz. per linear yd	
Width	54"	
Roll Size	60 yards	
Ends/Picks	Ends: 80 per inch Picks: 33 per inch	
Repeat	H - 2.438 " V - 1.0"	
Directional	Yes	
Railroaded	No	
Country of Origin	USA	

Additional Attributes

PFAS Free	In transition to PFAS Free Sku-Dependent
	Contact Customer Care
Certifications	
Greenguard Gold Certified	Yes - Crypton Technology is Greenguard Gold Certified
Recommended C	leaning
Please refer to Detaile	ed Cleaning Instructions.

Performance Characteristics

Abrasion Resistance ASTM D4157	100,000 double rubs*		
Brush Pill ASTM D3511	4		
Tensile Strength ASTM D5034	Warp: 243.0 lbs. Fill: 179.0 lbs.		
Tear Strength ASTM D2261	Warp: 45.0 lbs. Fill: 25.0 lbs.		
Seam Slippage ASTM D4034	Warp: 102.0 lbs. Fill: 69.0 lbs.		
Colorfastness to Crocking AATCC 8	Dry: 5.0 Wet: 4.5		
Colorfastness to Light AATCC 16	Hours: 40.0 Class: 4.0		
Flammability**			
CAL TB 117-2013	Passes		
NFPA 260	Class 1		
UFAC	Class 1		

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

 $\label{thm:continuous} Final\ determination\ of\ the\ suitability\ of\ this\ product\ for\ an\ application\ rests\ with\ the\ user.$

- * Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.
- ** This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.