
# Burch



Repeats Not Shown to Scale.

# Veranda Spring 1011971

Meets or exceeds all ACT® Standards

High Performance Vinyl Bleach Cleanable Indoor/Outdoor FR Free – Compliant with CAL AB 2998 PFAS Free CFFA-HC-201 Compliant



\*ACT® Registered Certification Marks

## **Fabric Specifications**

Face	100% Vinyl
Backing	100% Polyester
Finish/Treatment	Resilience™
Bleach Cleanable	Yes Ratio: 90% Water / 10% Bleach Solution
Indoor/Outdoor	Yes
Weight	32.0 oz. per linear yd
Thickness	1.02 mm
Width	54"
Roll Size	30 yards
Directional	Yes
Railroaded	No

### **Additional Attributes**

PFAS Free	Yes
CFFA-HC-201 Compliant	Yes
Prop 65 Compliant	Yes
Free of Added FR Chemicals / CAL AB2998 Compliant	Yes
Free of Added Anti-Bacterial Chemicals	Yes
Antimicrobial	Yes
BPA Free	Yes
Free of Conflict Minerals	Yes
Formaldehyde Free	Yes
Free of Heavy Metals	Yes
Lead Free	Yes
Mildew Resistant	Yes
Sulfide Stain Resistant	Yes

#### **Performance Characteristics**

Fill: 79.0 lbs.	Abrasion Resistance ASTM D4157	100,000 double rubs*
Fill: 12.8 lbs.	Tensile Strength cffA-17	
Fill: 43.2 lbs.	Tear Strength ASTM D751-06	
Wet: 5.0  UV Resistance 1000 hours  Adhesion ASTM D751-06 Warp: 7.6 lbs. Fill: 4.6 lbs.  Cold Crack CFFA-6 -20° F  Flex ASTM D2097-03 25,000 cycles  Flammability**  CAL TB 117-2013 Passes  NFPA 260 Class 1  UFAC Class 1	Seam Slippage ASTM D751-06	
Adhesion ASTM D751-06 Warp: 7.6 lbs. Fill: 4.6 lbs.  Cold Crack CFFA-6 -20° F  Flex ASTM D2097-03 25,000 cycles  Flammability**  CAL TB 117-2013 Passes  NFPA 260 Class 1  UFAC Class 1	Colorfastness to Crocking AATCC 8	,
Fill: 4.6 lbs.  Cold Crack CFFA-6 -20° F  Flex ASTM D2097-03 25,000 cycles  Flammability**  CAL TB 117-2013 Passes  NFPA 260 Class 1  UFAC Class 1	UV Resistance	1000 hours
Flammability**  CAL TB 117-2013 Passes  NFPA 260 Class 1  UFAC Class 1	Adhesion ASTM D751-06	
Flammability**           CAL TB 117-2013         Passes           NFPA 260         Class 1           UFAC         Class 1	Cold Crack CFFA-6	-20° F
CAL TB 117-2013 Passes  NFPA 260 Class 1  UFAC Class 1	Flex ASTM D2097-03	25,000 cycles
NFPA 260 Class 1 UFAC Class 1	Flammability**	
UFAC Class 1	CAL TB 117-2013	Passes
	NFPA 260	Class 1
FMVSS 302 Passes	UFAC	Class 1
	FMVSS 302	Passes

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

 $\label{thm:condition} Final\ determination\ of\ the\ suitability\ of\ this\ product\ for\ an\ application\ rests\ with\ the\ user.$ 

- \* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.
- \*\* This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

TRIS Free	Yes
HPD on File	Yes
Recommended Cleaning	
Please refer to Detailed Cleaning Instructions.	

Toll Free **1.800.841.8111** 

Visit us at **BurchFabrics.com**