# Burch



## Tulum Boardwalk 1012228

Meets or exceeds all ACT<sup>®</sup> Standards

Made in the USA High Performance Fabric Soil and Stain Repellent Bleach Cleanable Indoor/Outdoor PFAS Free



\*ACT<sup>®</sup> Registered Certification Marks

Repeats Not Shown to Scale.

#### **Fabric Specifications**

Content	100% Polyester UV	
Finish	InsideOut	
Backing	Acrylic	
Bleach Cleanable	Yes Ratio: 90% Water / 10% Bleach Solution	
Indoor/Outdoor	Yes	
Weight	25.1 oz. per linear yd	
Width	54"	
Roll Size	60 yards	
Ends/Picks	Ends: 80 per inch Picks: 54 per inch	
Repeat	H - 14.625 " V - 13.4 "	
Directional	Yes	
Railroaded	No	
Country of Origin	USA	

#### **Additional Attributes**

PFAS Free	Yes
InsideOut	Yes
HPD on File	Yes

### **Recommended Cleaning**

Please refer to Detailed Cleaning Instructions.

Performance Characteristics

Abrasion Resistance ASTM D4157	63,000 double rubs*		
Brush Pill ASTM D3511	3		
Tensile Strength ASTM D5034	Warp: 167.0 lbs. Fill: 419.0 lbs.		
Tear Strength ASTM D2261	Warp: 17.0 lbs. Fill: 41.0 lbs.		
Seam Slippage ASTM D4034	Warp: 76.0 lbs. Fill: 107.0 lbs.		
Colorfastness to Crocking AATCC 8	Dry: 4.0 Wet: 3.0		
Colorfastness to Light AATCC 16	Hours: 40.0 Class: 4.0		
Flammability**			
CAL TB 117-2013	Passes		
NFPA 260	Class 1		
UFAC	Class 1		

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

\* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

\*\* This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Toll Free 1.800.841.8111