# Burch



Repeats Not Shown to Scale

## Viceroy Antique Sage 1012259

Meets or exceeds all ACT® Standards

Crypton Seating Fabric PFAS Free

# **∀**A \*

\*ACT® Registered Certification Marks

#### **Fabric Specifications**

Content	64% Acrylic 33% Polyester 3% Viscose	
Finish	Crypton	
Backing	Crypton	
Weight	23.3 oz. per linear yd	
Width	54"	
Roll Size	35 yards	
Ends/Picks	Ends: 167 per inch Picks: 28 per inch	
Repeat	H - 14.0" V - 4.0"	
Directional	Yes	
Railroaded	No	
Country of Origin	Turkey	

### **Additional Attributes**

PFAS Free	Yes	
Certifications		
Greenguard Gold Certified	Yes - Crypton Technology is Greenguard Gold Certified	
Recommended Cleaning		
Please refer to Detailed Cleaning Instructions.		

#### **Performance Characteristics**

Abrasion Resistance ASTM D4157	70,000 double rubs*
Brush Pill ASTM D3511	5
Tensile Strength ASTM D5034	Warp: 349.5 lbs. Fill: 222.0 lbs.
Tear Strength ASTM D2261	Warp: 74.5 lbs. Fill: 55.8 lbs.
Seam Slippage ASTM D4034	Warp: 77.6 lbs. Fill: 97.0 lbs.
Colorfastness to Crocking AATCC 8	Dry: 4.0 Wet: 4.0
Colorfastness to Light AATCC 16	Hours: 40.0 Class: 4.0
Flammability**	
CAL TB 117-2013	Passes
NFPA 260	Class 1
UFAC	Class 1

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

- ${\rm *Abrasion\ test\ results\ exceeding\ ACT\ Performance\ Guidelines\ are\ not\ an\ indicator\ of\ product\ lifespan.\ Multiple\ factors\ affect\ fabric\ durability\ and\ appearance\ retention.}$
- \*\* This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.