# Burch



Repeats Not Shown to Scale.

## Java Bengal 1012666

Meets or exceeds all ACT® Standards

Made in the USA Crypton Seating Fabric Bleach Cleanable PFAS Free



\*ACT® Registered Certification Marks

### **Fabric Specifications**

Content 100% Polyester  Finish Crypton  Backing Crypton  Bleach Cleanable Yes Ratio: 90% Water / 10% Bleach Solution  Weight 28.3 oz. per linear yd  Width 54"  Roll Size 30 yards  Ends/Picks Ends: 145.78 per inch Picks: 62.92 per inch  Repeat H - 13.4 " V - 12.14 "  Directional Yes  Railroaded Yes  Country of Origin LISA		
Backing Crypton  Bleach Cleanable Yes Ratio: 90% Water / 10% Bleach Solution  Weight 28.3 oz. per linear yd  Width 54"  Roll Size 30 yards  Ends/Picks Ends: 145.78 per inch Picks: 62.92 per inch  Repeat H - 13.4 " V - 12.14 "  Directional Yes  Railroaded Yes	Content	100% Polyester
Bleach Cleanable	Finish	Crypton
Ratio: 90% Water / 10% Bleach Solution	Backing	Crypton
Width         54"           Roll Size         30 yards           Ends/Picks         Ends: 145.78 per inch Picks: 62.92 per inch           Repeat         H - 13.4 " V - 12.14 "           Directional         Yes           Railroaded         Yes	Bleach Cleanable	
Roll Size         30 yards           Ends/Picks         Ends: 145.78 per inch Picks: 62.92 per inch           Repeat         H - 13.4 " V - 12.14 "           Directional         Yes           Railroaded         Yes	Weight	28.3 oz. per linear yd
Ends/Picks Ends: 145.78 per inch Picks: 62.92 per inch  Repeat H - 13.4 " V - 12.14 "  Directional Yes  Railroaded Yes	Width	54"
Picks: 62.92 per inch  Repeat H - 13.4 " V - 12.14 "  Directional Yes  Railroaded Yes	Roll Size	30 yards
V - 12.14 "  Directional Yes  Railroaded Yes	Ends/Picks	
Railroaded Yes	Repeat	
	Directional	Yes
Country of Origin USA	Railroaded	Yes
obtainity of origin	Country of Origin	USA

#### **Additional Attributes**

PFAS Free	Yes	
Certifications		
Greenguard Gold Certified	Yes - Crypton Technology is Greenguard Gold Certified	
Recommended Cleaning		

#### **Performance Characteristics**

Abrasion Resistance ASTM D4157	100,000 double rubs*	
Brush Pill ASTM D3511	3	
Tensile Strength ASTM D5034	Warp: 271.1 lbs. Fill: 500.1 lbs.	
Tear Strength ASTM D2261	Warp: 90.0 lbs. Fill: 42.4 lbs.	
Seam Slippage ASTM D4034	Warp: 49.8 lbs. Fill: 65.4 lbs.	
Colorfastness to Crocking AATCC 8	Dry: 4.5 Wet: 4.5	
Colorfastness to Light AATCC 16	Hours: 40.0 Class: 4.0	
Flammability**		
CAL TB 117-2013	Passes	
NFPA 260	Class 1	
UFAC	Class 1	

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

 $\label{product} Final\ determination\ of\ the\ suitability\ of\ this\ product\ for\ an\ application\ rests\ with\ the\ user.$ 

- ${}^{\star}\,\text{Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.}$
- \*\* This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Please refer to Detailed Cleaning Instructions.