# Burch



Repeats Not Shown to Scale

## Palomino Tawny 1012708

Meets or exceeds all ACT® Standards

High Performance Vinyl Bleach Cleanable FR Free – Compliant with CAL AB 2998 PFAS Free



\*ACT® Registered Certification Marks

### **Fabric Specifications**

| Face 100% Vinyl  Backing 100% Polyester  Finish/Treatment Resilience™  Bleach Cleanable Yes Ratio: 90% Water / 10% Bleach Solution  Weight 32.0 oz. per linear yd  Thickness 1.30 mm  Width 54"  Roll Size 30 yards  Directional Yes  Railroaded No  Country of Origin Turkey |                   |                        |
|---|-------------------|------------------------|
| Finish/Treatment Resilience **  Bleach Cleanable Yes Ratio: 90% Water / 10% Bleach Solution  Weight 32.0 oz. per linear yd  Thickness 1.30 mm  Width 54*  Roll Size 30 yards  Directional Yes  Railroaded No  | Face              | 100% Vinyl             |
| Bleach Cleanable Yes Ratio: 90% Water / 10% Bleach Solution  Weight 32.0 oz. per linear yd  Thickness 1.30 mm  Width 54"  Roll Size 30 yards  Directional Yes  Railroaded No  | Backing           | 100% Polyester         |
| Ratio: 90% Water / 10% Bleach Solution  Weight 32.0 oz. per linear yd  Thickness 1.30 mm  Width 54"  Roll Size 30 yards  Directional Yes  Railroaded No   | Finish/Treatment  | Resilience™            |
| Thickness 1.30 mm  Width 54"  Roll Size 30 yards  Directional Yes  Railroaded No  | Bleach Cleanable  |                        |
| Width 54"  Roll Size 30 yards  Directional Yes  Railroaded No   | Weight            | 32.0 oz. per linear yd |
| Roll Size 30 yards  Directional Yes  Railroaded No  | Thickness         | 1.30 mm                |
| Directional Yes Railroaded No   | Width             | 54"                    |
| Railroaded No   | Roll Size         | 30 yards               |
|   | Directional       | Yes                    |
| Country of Origin Turkey  | Railroaded        | No                     |
|   | Country of Origin | Turkey                 |

#### **Additional Attributes**

| PFAS Free   | Yes |
|---|-----|
| Prop 65 Compliant                                 | Yes |
| 16P Phthalate Free                                | Yes |
| Free of Added FR Chemicals / CAL AB2998 Compliant | Yes |
| Antibacterial                                     | Yes |
| Antimicrobial                                     | Yes |
| BPA Free  | Yes |
| Free of Conflict Minerals                         | Yes |
| Formaldehyde Free                                 | Yes |
| Free of Heavy Metals                              | Yes |
| Lead Free   | Yes |
| Sulfide Stain Resistant                           | Yes |
| TRIS Free   | Yes |
|   |     |

#### **Performance Characteristics**

| Abrasion Resistance ASTM D4157    | 250,000 double rubs*                 |
|-----------------------------------|--------------------------------------|
| Tensile Strength ASTM D751-06     | Warp: 175.0 lbs.<br>Fill: 163.0 lbs. |
| Tear Strength ASTM D2261          | Warp: 11.2 lbs.<br>Fill: 18.9 lbs.   |
| Seam Slippage ASTM D751           | Warp: 60.7 lbs.<br>Fill: 79.1 lbs.   |
| Colorfastness to Crocking AATCC 8 | Dry: 5.0<br>Wet: 5.0                 |
| UV Resistance AATCC 16            | 300 hours                            |
| Adhesion ASTM D751-06             | Warp: 7.4 lbs.<br>Fill: 6.1 lbs.     |
| Cold Crack cffA-6                 | -20° F                               |
| Flex ASTM D2097                   | 25,000 cycles                        |
| Flammability**                    |                                      |
| CAL TB 117-2013                   | Passes                               |
| NFPA 260                          | Class 1                              |

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

<sup>\*</sup> Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

<sup>\*\*</sup> This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

| Recommen        | ded Cleaning                    |
|-----------------|---------------------------------|
| Please refer to | Detailed Cleaning Instructions. |

Toll Free **1.800.841.8111** 

Visit us at **BurchFabrics.com**