# Burch



Repeats Not Shown to Scale

## Palomino Tawny 1012708

Meets or exceeds all ACT® Standards

High Performance Vinyl Bleach Cleanable FR Free – Compliant with CAL AB 2998 PFAS Free



\*ACT® Registered Certification Marks

### **Fabric Specifications**

Face 100% Vinyl  Backing 100% Polyester  Finish/Treatment Resilience™  Bleach Cleanable Yes Ratio: 90% Water / 10% Bleach Solution  Weight 32.0 oz. per linear yd  Thickness 1.30 mm  Width 54"  Roll Size 30 yards  Directional Yes  Railroaded No  Country of Origin Turkey		
Finish/Treatment Resilience **  Bleach Cleanable Yes Ratio: 90% Water / 10% Bleach Solution  Weight 32.0 oz. per linear yd  Thickness 1.30 mm  Width 54*  Roll Size 30 yards  Directional Yes  Railroaded No	Face	100% Vinyl
Bleach Cleanable Yes Ratio: 90% Water / 10% Bleach Solution  Weight 32.0 oz. per linear yd  Thickness 1.30 mm  Width 54"  Roll Size 30 yards  Directional Yes  Railroaded No	Backing	100% Polyester
Ratio: 90% Water / 10% Bleach Solution  Weight 32.0 oz. per linear yd  Thickness 1.30 mm  Width 54"  Roll Size 30 yards  Directional Yes  Railroaded No	Finish/Treatment	Resilience™
Thickness 1.30 mm  Width 54"  Roll Size 30 yards  Directional Yes  Railroaded No	Bleach Cleanable	
Width 54"  Roll Size 30 yards  Directional Yes  Railroaded No	Weight	32.0 oz. per linear yd
Roll Size 30 yards  Directional Yes  Railroaded No	Thickness	1.30 mm
Directional Yes Railroaded No	Width	54"
Railroaded No	Roll Size	30 yards
	Directional	Yes
Country of Origin Turkey	Railroaded	No
	Country of Origin	Turkey

#### **Additional Attributes**

PFAS Free	Yes
Prop 65 Compliant	Yes
16P Phthalate Free	Yes
Free of Added FR Chemicals / CAL AB2998 Compliant	Yes
Antibacterial	Yes
Antimicrobial	Yes
BPA Free	Yes
Free of Conflict Minerals	Yes
Formaldehyde Free	Yes
Free of Heavy Metals	Yes
Lead Free	Yes
Sulfide Stain Resistant	Yes
TRIS Free	Yes

#### **Performance Characteristics**

Abrasion Resistance ASTM D4157	250,000 double rubs*
Tensile Strength ASTM D751-06	Warp: 175.0 lbs. Fill: 163.0 lbs.
Tear Strength ASTM D2261	Warp: 11.2 lbs. Fill: 18.9 lbs.
Seam Slippage ASTM D751	Warp: 60.7 lbs. Fill: 79.1 lbs.
Colorfastness to Crocking AATCC 8	Dry: 5.0 Wet: 5.0
UV Resistance AATCC 16	300 hours
Adhesion ASTM D751-06	Warp: 7.4 lbs. Fill: 6.1 lbs.
Cold Crack cffA-6	-20° F
Flex ASTM D2097	25,000 cycles
Flammability**	
CAL TB 117-2013	Passes
NFPA 260	Class 1

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

<sup>\*</sup> Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

<sup>\*\*</sup> This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Recommended Cleanin	g
Please refer to Detailed Cleaning Instructions.	

Toll Free **1.800.841.8111** 

Visit us at **BurchFabrics.com**