Burch



Fairfax Flamenco

1012922

Meets or exceeds all ACT[®] Standards

High Performance Fabric Soil and Stain Repellent PFAS Free



Repeats Not Shown to Scale

Fabric Specifications

Content	53% Olefin	
	41% Acrylic	
	6% Polyester	
Finish	PFAS Free Soil and Stain Repellent	
Backing	Acrylic	
Weight	20.8 oz. per linear yd	
Width	54"	
Roll Size	50 yards	
Ends/Picks	Ends: 30 per inch	
	Picks: 25 per inch	
Directional	Yes	
Deflered ed	A1 -	
Railroaded	No	
Country of Origin	Turkey	
	-	

Additional Attributes

PFAS Free	Yes
High Performance	Yes

Recommended Cleaning

Please refer to Detailed Cleaning Instructions.

Performance Characteristics

Abrasion Resistance ASTM D4157	100,000 double rubs*	
Brush Pill ASTM D3511	4	
Tensile Strength ASTM D5034	Warp: 289.0 lbs. Fill: 271.0 lbs.	
Tear Strength ASTM D2261	Warp: 45.0 lbs. Fill: 74.6 lbs.	
Seam Slippage ASTM D4034	Warp: 51.4 lbs. Fill: 92.7 lbs.	
Colorfastness to Crocking AATCC 8	Dry: 4.0 Wet: 4.0	
Colorfastness to Light AATCC 16	Hours: 40.0 Class: 5.0	
Flammability**		
CAL TB 117-2013	Passes	
NFPA 260	Class 1	

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

** This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Toll Free 1.800.841.8111

Visit us at BurchFabrics.com