Burch



Repeats Not Shown to Scale.

Fabric Specifications

Face	100% PVC Free Polyurethane	
Backing	100% Polyester	
Bleach Cleanable	Yes Ratio: 90% Water / 10% Bleach Solution	
Weight	16.5 oz. per linear yd	
Thickness	.85 mm	
Width	54"	
Roll Size	30 yards	
Directional	No	
Railroaded	No	

Additional Attributes

PFAS Free	Yes
PVC Free	Yes
Prop 65 Compliant	Yes
16P Phthalate Free	Yes
Free of Added FR Chemicals / CAL AB2998 Compliant	Yes
Free of Added Anti-Bacterial Chemicals	Yes
Free of Added Anti-Microbial Chemicals	Yes
BPA Free	Yes
Free of Conflict Minerals	Yes
Formaldehyde Free	Yes
Free of Heavy Metals	Yes
Lead Free	Yes
Sulfide Stain Resistant	Yes
TRIS Free	Yes
Low VOC	Yes

Elite Flame 1007054

Meets or exceeds all ACT® Standards

PVC Free Polyurethane Bleach Cleanable FR Free – Compliant with CAL AB 2998 PFAS Free



*ACT® Registered Certification Marks

Performance Characteristics

Abrasion Resistance ASTM D4157	250,000 double rubs*	
Tensile Strength CFFA-17	Warp: 143.0 lbs. Fill: 105.0 lbs.	
Tear Strength CFFA-16	Warp: 7.4 lbs. Fill: 12.7 lbs.	
Seam Slippage CFFA-14	Warp: 55.9 lbs. Fill: 44.9 lbs.	
Colorfastness to Crocking AATCC 8	Dry: 5.0 Wet: 5.0	
UV Resistance CFFA-2	200 hours	
Adhesion CFFA-3	Warp: 10.3 lbs. Fill: 9.1 lbs.	
Blocking CFFA-4	1	
Cold Crack CFFA-6	-20° F	
Flex CFFA-10	25,000 cycles	
Hydrolysis	5 Weeks	
Flammability**		
CAL TB 117-2013	Passes	
NFPA 260	Class 1	
UFAC	Class 1	

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

The use of polyurethane for welt cord in upholstery applications is strongly discouraged. Even though Burch's polyurethane products are designed to exceed industry abrasion standards, when used with welt cord the exposed material becomes more vulnerable to abrasion and may experience premature de-lamination. Burch cannot be held responsible for damage that may occur when used in a welt cord application.

Final determination of the suitability of this product for an application rests with the user.

* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

** This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions. **Recommended Cleaning**

Please refer to Detailed Cleaning Instructions.

Toll Free 1.800.841.8111

Visit us at BurchFabrics.com