
Burch



Prodigy Black 1006626

Meets or exceeds all ACT[®] Standards

High Performance Vinyl

Indoor/Outdoor PFAS Free



Repeats Not Shown to Scale.

Fabric Specifications

| Face | 100% Vinyl |
|-------------------|-------------------------|
| Backing | 100% Polyester |
| Finish/Treatment | Stain Resistant Finish |
| Indoor/Outdoor | Yes |
| Weight | 30.75 oz. per linear yd |
| Thickness | 1.22 mm |
| Width | 54" |
| Roll Size | 40 yards |
| Directional | No |
| Railroaded | No |
| Country of Origin | Canada |
| | |

Additional Attributes

| PFAS Free | Yes |
|---------------------------|-----|
| 16P Phthalate Free | Yes |
| Antibacterial | Yes |
| Antimicrobial | Yes |
| BPA Free | Yes |
| Free of Conflict Minerals | Yes |
| Formaldehyde Free | Yes |
| Free of Heavy Metals | Yes |
| Lead Free | Yes |
| Mildew Resistant | Yes |
| Sulfide Stain Resistant | Yes |
| TRIS Free | Yes |
| Low VOC | Yes |
| | |

Performance Characteristics

| Abrasion Resistance ASTM D4157 | 100,000 double rubs* |
|-----------------------------------|-------------------------------------|
| Tensile Strength CFFA-17 | Warp: 110.0 lbs. Fill: 75.0 lbs. |
| Tear Strength Fed Std 191A-5134 | Warp: 8.0 lbs. Fill: 10.0 lbs. |
| Colorfastness to Crocking AATCC 8 | Dry: 4.0-5.0 Wet: 4.0-5.0 |
| UV Resistance CFFA-2 | 1000 hours |
| Adhesion CFFA-3 | Warp: 3.5 lbs. Fill: 3.5 lbs. |
| Blocking CFFA-4 | 2 |
| Cold Crack CFFA-6 | -25° F |
| Flex ASTM D2097-03 | 30,000 cycles |
| Flammability** | |
| CAL TB 117-2013 | Passes |
| NFPA 260 | Class 1 |
| UFAC | Class 1 |
| FMVSS 302 | Passes |
| | |

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

Proposition 65 Warning: Yes

* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

** This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Recommended Cleaning

Please refer to Detailed Cleaning Instructions.

Toll Free 1.800.841.8111

Visit us at BurchFabrics.com