



Repeats Not Shown to Scale.

Vintage Wicker SVI-015

Meets or exceeds all ACT[®] Standards

High Performance Vinyl

FR Free – Compliant with CAL AB 2998
PFAS Free



*ACT[®] Registered Certification Marks

Fabric Specifications

| | |
|------------------|------------------------------|
| Face | 100% Vinyl |
| Backing | 75% Polyester, 25% Cotton |
| Finish/Treatment | Standard Acrylic Topcoat |
| Weight | 36.0 oz. per linear yd |
| Thickness | 1.10 mm |
| Width | 54" |
| Roll Size | 30 yards |
| Directional | Yes |
| Railroaded | No |

Additional Attributes

| | |
|---|-----|
| PFAS Free | Yes |
| Prop 65 Compliant | Yes |
| 16P Phthalate Free | Yes |
| Free of Added FR Chemicals / CAL AB2998 Compliant | Yes |
| Free of Added Anti-Bacterial Chemicals | Yes |
| Free of Added Anti-Microbial Chemicals | Yes |
| BPA Free | Yes |
| Free of Conflict Minerals | Yes |
| Formaldehyde Free | Yes |
| Lead Free | Yes |
| TRIS Free | Yes |

Recommended Cleaning

Please refer to Detailed Cleaning Instructions.

Performance Characteristics

| | |
|--|------------------------------------|
| Abrasion Resistance <small>ASTM D4157</small> | 50,000 double rubs* |
| Tensile Strength <small>CFFA-17</small> | Warp: 67.0 lbs. Fill: 83.0 lbs. |
| Tear Strength <small>CFFA-16</small> | Warp: 5.6 lbs. Fill: 6.2 lbs. |
| Seam Slippage <small>CFFA-14</small> | Warp: 68.0 lbs. Fill: 65.0 lbs. |
| Colorfastness to Crocking <small>AATCC 8</small> | Dry: 4.5 Wet: 4.0 |
| UV Resistance <small>CFFA-2</small> | 300 hours |
| Adhesion <small>CFFA-3</small> | Warp: 9.7 lbs. Fill: 9.9 lbs. |
| Cold Crack <small>CFFA-6</small> | -20° F |
| Flex <small>CFFA-10</small> | 25,000 cycles |

Flammability**

| | |
|--------------------------------|--------------|
| CAL TB 117-2013 | Passes |
| NFPA 260 | Class 1 |
| UFAC | Class 1 |
| ASTM E-84 | Class A or 1 |
| BIFMA CS-191-53, Sec. 3 | Passes |
| BIFMA Upholstery, Sec. 4 | Passes |
| IMO 2010 FTP Part 8, 3.1 & 3.2 | Passes |
| FMVSS 302 | Passes |

Vintage is specifically formulated to emulate the appearance of the fine waxed pull-up leather. It is designed to distress and lighten when it is sewn and tufted, stretched or creased. NOTE: Folding the material and keeping it folded over long periods of time in production could result in crease marks that may not come out.

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

** This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Toll Free **1.800.841.8111**

Visit us at **BurchFabrics.com**