



Repeats Not Shown to Scale.

Footnote Fern 1007897

Meets or exceeds all ACT® Standards

- PVC Free Polyurethane
- Ink Cleanable
- Denim Dye Cleanable
- Bleach Cleanable



*ACT® Registered Certification Marks

Fabric Specifications

Face	100% PVC Free Polyurethane
Backing	100% Polyester
Weight	20.0 oz. per linear yd
Thickness	1.00 mm
Width	54"
Roll Size	30 yards
Directional	Yes
Railroaded	No

Additional Attributes

Ink Cleanable	Yes
Denim Dye Cleanable	Yes
PVC Free	Yes
Bleach Cleanable	Yes Ratio: 80% Water / 20% Bleach Solution
Antibacterial	Yes
Antimicrobial	Yes
BPA Free	Yes
Formaldehyde Free	Yes
Free of Conflict Minerals	Yes
Lead Free	Yes
Mildew Resistant	Yes
16P Phthalate Free	Yes
Sulfide Stain Resistant	Yes
TRIS Free	Yes

Recommended Cleaning

Performance Characteristics

Abrasion Resistance <small>ASTM D4157</small>	150,000 double rubs*
Tensile Strength <small>CFFA-17</small>	Warp: 144.0 lbs. Fill: 113.0 lbs.
Tear Strength <small>CFFA-16b</small>	Warp: 5.1 lbs. Fill: 2.9 lbs.
Seam Slippage	Warp: 59.6 lbs. Fill: 44.4 lbs.
Colorfastness to Crocking <small>AATCC 8</small>	Dry: 5.0 Wet: 5.0
UV Resistance <small>CFFA-2</small>	200 hours
Adhesion <small>CFFA-3</small>	Warp: 11.4 lbs. Fill: 10.8 lbs.
Blocking <small>CFFA-4</small>	1
Cold Crack <small>CFFA-6</small>	-20° F
Flex <small>CFFA-10</small>	25,000 cycles
Hydrolysis	7 Weeks

Flammability**

CAL TB 117-E	Passes
NFPA 260	Class 1
UFAC	Class 1
ASTM E-84	Passes
IMO 2010 FTP Part 8, 3.1	Passes
FMVSS 302	Passes

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

The use of polyurethane for welt cord in upholstery applications is strongly discouraged. Even though Burch's polyurethane products are designed to exceed industry abrasion standards, when used with welt cord the exposed material becomes more vulnerable to abrasion and may experience premature de-lamination. Burch cannot be held responsible for damage that may occur when used in a welt cord application.

Please refer to Detailed Cleaning Instructions.

Final determination of the suitability of this product for an application rests with the user.

* Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

** This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.
Final determination of the suitability of this product for an application rests with the user.

Toll Free **1.800.841.8111**

Visit us at **BurchFabrics.com**