



Repeats Not Shown to Scale.

Fortress Dill / 1009030

Meets or exceeds all ACT® Standards

High Performance Vinyl
Ink Cleanable



*ACT® Registered Certification Marks

Fabric Specifications

Face	100% Vinyl
Backing	100% Polyester
Weight	30.0 oz. per linear yd
Thickness	1.02 mm
Width	54"
Directional	Yes
Railroaded	No

Additional Attributes

Finish/Treatment	MGX MorGuard Xtreme™
Ink Cleanable	Yes
Antibacterial	Yes
Antimicrobial	Yes
Bleach Cleanable	Yes Ratio: 90% Water / 10% Bleach Solution
Sulfide Stain Resistant	Yes
Ink Cleanable	Yes

Recommended Cleaning

Please refer to Detailed Cleaning Instructions.

Performance Characteristics

Abrasion Resistance ASTM D4157	100,000 double rubs
Tensile Strength CFFA-17	Warp: 110.0 lbs. Fill: 80.0 lbs.
Tear Strength CFFA-16	Warp: 12.0 lbs. Fill: 10.0 lbs.
Colorfastness to Crocking AATCC 8	Dry: 4.5 Wet: 4.5
UV Resistance CFFA-2	120 hours
Adhesion CFFA-3	Warp: 3.0 lbs. Fill: 3.0 lbs.
Blocking CFFA-4	2
Cold Crack CFFA-6	-25° F
Flex CFFA-10	30,000 cycles

Flammability**

CAL TB 117-2013	Passes
NFPA 260	Class 1
UFAC	Class 1

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

** This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.
Final determination of the suitability of this product for an application rests with the user.

