



Repeats Not Shown to Scale.

Motive Jet / 1009328

Meets or exceeds all ACT® Standards

High Performance Vinyl
Bleach Cleanable



*ACT® Registered Certification Marks

Fabric Specifications

Face	100% Vinyl
Backing	100% Polyester
Weight	30.0 oz. per linear yd
Thickness	1.00 mm
Width	54"
Ends/Picks	Ends: 0 per inch Picks: 0 per inch
Directional	Yes
Railroaded	No

Additional Attributes

Resilience™	Yes
Bleach Cleanable	Yes Ratio: 90% Water / 10% Bleach Solution
BPA Free	Yes
Formaldehyde Free	Yes
Free of Added FR Chemicals	Yes
Free of Conflict Minerals	Yes
Lead Free	Yes
16P Phthalate Free	Yes
Sulfide Stain Resistant	Yes
TRIS Free	Yes

Recommended Cleaning

Please refer to Detailed Cleaning Instructions.

Performance Characteristics

Abrasion Resistance ASTM D4157	100,000 double rubs
Tensile Strength CFFA-17	Warp: 101.0 lbs. Fill: 93.0 lbs.
Tear Strength CFFA-16	Warp: 6.8 lbs. Fill: 8.0 lbs.
Seam Slippage	Warp: 50.0 lbs. Fill: 50.0 lbs.
Colorfastness to Crocking AATCC 8	Dry: 5.0 Wet: 5.0
UV Resistance CFFA-2	300 hours
Adhesion CFFA-3	Warp: 10.27 lbs. Fill: 11.5 lbs.
Cold Crack CFFA-6	-20° F

Flammability**

CAL TB 117-2013	Passes
NFPA 260	Class 1
UFAC	Class 1

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

Proposition 65 Warning: Yes

** This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.
Final determination of the suitability of this product for an application rests with the user.

Toll Free **1.800.841.8111**

Visit us at **BurchFabrics.com**