

Bandwidth Riviera 1009783

Meets or exceeds all ACT[®] Standards

High Performance Vinyl Bleach Cleanable PFAS Free



Repeats Not Shown to Scale.

Fabric Specifications

Face	100% Vinyl
Backing	100% Polyester
Finish/Treatment	PRODURATECT™ PLUS
Bleach Cleanable	Yes Ratio: 90% Water / 10% Bleach Solution
Weight	28.0 oz. per linear yd
Thickness	1.00 mm
Width	54"
Roll Size	30 yards
Directional	Yes
Railroaded	No

Additional Attributes

PFAS Free	Yes
Antibacterial	Yes
Antimicrobial	Yes
BPA Free	Yes
Free of Conflict Minerals	Yes
Formaldehyde Free	Yes
Lead Free	Yes
Sulfide Stain Resistant	Yes
TRIS Free	Yes
Recommended Cleaning	
Please refer to Detailed Cleaning Instructions.	

Performance Characteristics

Abrasion Resistance ASTM D4157	100,000 double rubs*	
Tensile Strength ASTM D751	Warp: 165.0 lbs. Fill: 83.0 lbs.	
Tear Strength ASTM D751	Warp: 39.0 lbs. Fill: 32.0 lbs.	
UV Resistance ASTM G154	500 hours	
Adhesion ASTM D751	Warp: 6.0 lbs. Fill: 6.0 lbs.	
Cold Crack CFFA-6	-10° F	
Flammability**		
CAL TB 117-2013	Passes	
NFPA 260	Class 1	
UFAC	Class 1	
FMVSS 302	Passes	

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

Proposition 65 Warning: Yes

* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

** This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Toll Free 1.800.841.8111