



Repeats Not Shown to Scale.

## Sedona Tumbleweed 1011241

Meets or exceeds all ACT® Standards

High Performance Vinyl

PFAS Free



\*ACT® Registered Certification Marks

### Fabric Specifications

Face	100% Vinyl
Backing	100% Polyester
Weight	32.0 oz. per linear yd
Thickness	1.02 mm
Width	54"
Roll Size	30 yards
Directional	Yes
Railroaded	No

### Additional Attributes

PFAS Free	Yes
Antibacterial	Yes
Antimicrobial	Yes
BPA Free	Yes
Free of Conflict Minerals	Yes
Formaldehyde Free	Yes
Free of Heavy Metals	Yes
Lead Free	Yes
TRIS Free	Yes
Low VOC	Yes

### Recommended Cleaning

Please refer to Detailed Cleaning Instructions.

### Performance Characteristics

Abrasion Resistance <small>ASTM D4157</small>	100,000 double rubs*
Tensile Strength <small>ASTM D751-06</small>	Warp: 130.0 lbs. Fill: 85.0 lbs.
Tear Strength <small>ASTM D751-06</small>	Warp: 8.0 lbs. Fill: 8.0 lbs.
Colorfastness to Crocking <small>AATCC 8</small>	Dry: 4.0 Wet: 4.0
UV Resistance <small>ASTM D4329</small>	300 hours
Adhesion <small>CFFA-3</small>	Warp: 4.5 lbs. Fill: 4.5 lbs.
Blocking <small>CFFA-4</small>	4
Cold Crack <small>CFFA-6</small>	-10° F

### Flammability\*\*

CAL TB 117-2013	Passes
NFPA 260	Class 1
UFAC	Class 1
FMVSS 302	Passes

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

Proposition 65 Warning: Yes

\* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

\*\* This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.