



Repeats Not Shown to Scale.

Classic Water / SCL-115

Meets or exceeds all ACT® Standards

High Performance Vinyl
Bleach Cleanable



*ACT® Registered Certification Marks

Fabric Specifications

Face	100% Vinyl
Backing	100% Polyester
Weight	29.0 oz. per linear yd
Thickness	1.20 mm
Width	54"
Ends/Picks	Ends: 0 per inch Picks: 0 per inch
Directional	No
Railroaded	No

Additional Attributes

Resilience™	Yes
Bleach Cleanable	Yes Ratio: 90% Water / 10% Bleach Solution
Antibacterial	Yes
Antimicrobial	Yes
Mildew Resistant	Yes
Sulfide Stain Resistant	Yes

Recommended Cleaning

Please refer to Detailed Cleaning Instructions.

Performance Characteristics

Abrasion Resistance <small>ASTM D4157</small>	500,000 double rubs*
Tensile Strength <small>CFFA-17</small>	Warp: 142.0 lbs. Fill: 97.0 lbs.
Tear Strength <small>CFFA-16</small>	Warp: 7.9 lbs. Fill: 7.7 lbs.
Seam Slippage	Warp: 58.0 lbs. Fill: 41.0 lbs.
Colorfastness to Crocking <small>AATCC 8</small>	Dry: 5.0 Wet: 5.0
UV Resistance <small>CFFA-2</small>	500 hours
Adhesion <small>CFFA-3</small>	Warp: 12.1 lbs. Fill: 9.8 lbs.
Blocking <small>CFFA-4</small>	2
Cold Crack <small>CFFA-6</small>	-20° F
Flex <small>CFFA-10</small>	25,000 cycles

Flammability**

CAL TB 117-E	Passes
NFPA 260	Class 1
UFAC	Class 1
ASTM E-84	Class A or 1
BIFMA CS-191-53, Sec. 3	Passes
BIFMA Upholstery, Sec. 4	Passes
Boston Fire Code	Passes
IMO 2010 FTP Part 8, 3.1 & 3.2	Passes
FMVSS 302	Passes
Port Authority of NY/NJ	Passes

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

Proposition 65 Warning: Yes

* Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

** This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.
Final determination of the suitability of this product for an application rests with the user.

Toll Free **1.800.841.8111**

Visit us at **BurchFabrics.com**